Exhibit A

to

Complaint
for Patent Infringement

The ’054 Patent

US009198054B2

(12) **United States Patent**
Cuff et al.

(10) **Patent No.: US 9,198,054 B2**
(45) **Date of Patent: *Nov. 24, 2015**

(54) **AGGREGATE LOCATION DYNOMETER (ALD)**

(71) Applicant: **TeleCommunication Systems, Inc.**, Annapolis, MD (US)

(72) Inventors: **Michael A. Cuff**, Clyde Hill, WA (US); **Todd Gehrke**, Seattle, WA (US); **Farhad Kasad**, Bothell, WA (US)

(73) Assignee: **TeleCommunication Systems, Inc.**, Annapolis, MD (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/176,691**

(22) Filed: **Feb. 10, 2014**

(65) **Prior Publication Data**

US 2014/0155105 A1 Jun. 5, 2014

Related U.S. Application Data

(63) Continuation of application No. 13/317,996, filed on Nov. 2, 2011, now Pat. No. 8,649,806.

(60) Provisional application No. 61/573,112, filed on Sep. 2, 2011.

(51) **Int. Cl.**
H04W 24/00 (2009.01)
H04W 24/08 (2009.01)
(Continued)

(52) **U.S. Cl.**
CPC ***H04W 24/00*** (2013.01); ***H04W 4/023*** (2013.01); ***H04W 24/08*** (2013.01); ***H04W 64/006*** (2013.01); *H04L 67/22* (2013.01); *H04W 4/22* (2013.01)

(58) **Field of Classification Search**
CPC H04W 64/006; H04W 4/22; H04W 4/02; H04W 4/028; H04W 76/007; H04W 4/023; H04W 24/00; H04W 4/025; H04W 24/08; H04W 64/00; H04L 67/22
USPC 455/404.1, 404.2, 456.1–457, 405, 455/456.6, 456.2, 456.3, 456.5, 435.1, 455/435.2
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,445,118 A 4/1984 Taylor
4,928,107 A 5/1990 Kuroda
(Continued)

OTHER PUBLICATIONS

International Search Report received in PCT/US2012/000374 dated Nov. 20, 2012.
(Continued)

Primary Examiner — Olumide T Ajibade Akonai
(74) *Attorney, Agent, or Firm* — William H. Bollman

(57) **ABSTRACT**

An Aggregate Location Dynometer (ALD) in a physical wireless network alerts to a problematic crowd risk using location based services (LBS). An Aggregate Location Dynometer (ALD) comprises a Network Monitor, a Crowd Risk Determinant and an Alert Module. The Network Monitor monitors wireless traffic for a potential viral event, associated with a formation of a plurality of wireless devices. The Crowd Risk Determinant requests location information associated with a plurality of wireless devices in a given area regarding a respective viral event. The Crowd Risk Determinant determines if the viral event also indicates a crowd safety risk, based on the shape and movement of observed wireless devices. The Alert Module triggers an alert of an impending crowd problem when crowd risk is above a given threshold. Historical databases are empirically determined and maintained in the Aggregate Location Dynometer (ALD) for use in viral event and crowd risk assessment.

14 Claims, 7 Drawing Sheets



(51) **Int. Cl.**

H04W 64/00	(2009.01)
H04W 4/02	(2009.01)
H04L 29/08	(2006.01)
H04W 4/22	(2009.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,972,484	A	11/1990	Theile
5,126,722	A	6/1992	Kamis
5,283,570	A	2/1994	Deluca
5,301,354	A	4/1994	Schwendeman
5,311,516	A	5/1994	Kuznicki
5,327,529	A	7/1994	Fults
5,335,246	A	8/1994	Yokev
5,351,235	A	9/1994	Lahtinen
5,365,451	A	11/1994	Wang
5,418,537	A	5/1995	Bird
5,422,813	A	6/1995	Schuchman
5,479,408	A	12/1995	Will
5,485,163	A	1/1996	Singer
5,504,491	A	4/1996	Chapman
5,506,886	A	4/1996	Maine
5,517,199	A	5/1996	DiMattei
5,530,655	A	6/1996	Lokhoff
5,530,914	A	6/1996	McPheters
5,539,395	A	7/1996	Buss
5,539,829	A	7/1996	Lokhoff
5,546,445	A	8/1996	Dennison
5,568,153	A	10/1996	Beliveau
5,583,774	A	12/1996	Diesel
5,594,780	A	1/1997	Wiedeman
5,606,618	A	2/1997	Lokhoff
5,629,693	A	5/1997	Janky
5,633,630	A	5/1997	Park
5,636,276	A	6/1997	Brugger
5,661,652	A	8/1997	Sprague
5,661,755	A	8/1997	Van de Kerkhof
5,689,245	A	11/1997	Noreen
5,699,053	A	12/1997	Jonsson
5,704,029	A	12/1997	Wright, Jr.
5,721,781	A	2/1998	Deo
5,727,057	A	3/1998	Emery
5,731,785	A	3/1998	Lemelson
5,765,152	A	6/1998	Erickson
5,771,353	A	6/1998	Eggleston
5,774,670	A	6/1998	Montulli
5,809,415	A	9/1998	Rossman
5,812,086	A	9/1998	Bertiger
5,812,087	A	9/1998	Krasner
5,841,396	A	11/1998	Krasner
5,857,201	A	1/1999	Wright, Jr.
5,864,667	A	1/1999	Barkam
5,874,914	A	2/1999	Krasner
5,896,369	A	4/1999	Warsta
5,922,074	A	7/1999	Richard
5,930,250	A	7/1999	Klok
5,945,944	A	8/1999	Krasner
5,946,629	A	8/1999	Sawyer
5,950,137	A	9/1999	Kim
5,960,362	A	9/1999	Grob
5,983,099	A	11/1999	Yao
5,999,124	A	12/1999	Sheynblat
6,032,051	A	2/2000	Hall
6,049,718	A	4/2000	Stewart
6,052,081	A	4/2000	Krasner
6,058,338	A	5/2000	Agashe
6,061,018	A	5/2000	Sheynblat
6,064,336	A	5/2000	Krasner
6,067,045	A	5/2000	Castelloe
6,081,229	A	6/2000	Soliman
6,085,320	A	7/2000	Kaliski, Jr.
6,118,403	A	9/2000	Lang
6,121,923	A	9/2000	King
6,124,810	A	9/2000	Segal
6,131,067	A	10/2000	Girerd
6,133,874	A	10/2000	Krasner
6,134,483	A	10/2000	Vayanos
6,147,598	A	11/2000	Murphy
6,150,980	A	11/2000	Krasner
6,154,172	A	11/2000	Piccionelli
6,169,901	B1	1/2001	Boucher
6,169,902	B1	1/2001	Kawamoto
6,178,506	B1	1/2001	Quick, Jr.
6,185,427	B1	2/2001	Krasner
6,188,354	B1	2/2001	Soliman
6,188,909	B1	2/2001	Alanara
6,189,098	B1	2/2001	Kaliski, Jr.
6,195,557	B1	2/2001	Havinis
6,204,798	B1	3/2001	Fleming
6,205,330	B1	3/2001	Winbladh
6,208,290	B1	3/2001	Krasner
6,215,441	B1	4/2001	Moeglein
6,239,742	B1	5/2001	Krasner
6,247,135	B1	6/2001	Feague
6,249,873	B1	6/2001	Richard
6,253,203	B1	6/2001	O'Flaherty
6,260,147	B1	7/2001	Quick, Jr.
6,275,692	B1	8/2001	Skog
6,275,849	B1	8/2001	Ludwig
6,297,768	B1	10/2001	Allen, Jr.
6,307,504	B1	10/2001	Sheynblat
6,308,269	B2	10/2001	Proidl
6,313,786	B1	11/2001	Sheynblat
6,321,257	B1	11/2001	Kotola
6,324,542	B1	11/2001	Lent
6,327,473	B1	12/2001	Soliman
6,333,919	B2	12/2001	Gaffney
6,360,093	B1	3/2002	Ross
6,360,102	B1	3/2002	Havinis
6,363,254	B1	3/2002	Jones
6,367,019	B1	4/2002	Ansell
6,370,389	B1	4/2002	Isomursu
6,377,209	B1	4/2002	Krasner
6,400,314	B1	6/2002	Krasner
6,400,958	B1	6/2002	Isomursu
6,411,254	B1	6/2002	Moeglein
6,421,002	B2	7/2002	Krasner
6,430,504	B1	8/2002	Gilbert
6,433,734	B1	8/2002	Krasner
6,442,391	B1	8/2002	Johansson
6,449,473	B1	9/2002	Raivisto
6,449,476	B1	9/2002	Hutchison, IV
6,456,852	B2	9/2002	Bar
6,463,272	B1	10/2002	Wallace
6,477,150	B1	11/2002	Maggenti
6,505,049	B1	1/2003	Dorenbosch
6,510,387	B2	1/2003	Fuchs
6,512,922	B1	1/2003	Burg
6,512,930	B2	1/2003	Sandegren
6,515,623	B2	2/2003	Johnson
6,519,466	B2	2/2003	Pande
6,522,682	B1	2/2003	Kohli
6,525,687	B2	2/2003	Roy
6,525,688	B2	2/2003	Chou
6,529,829	B2	3/2003	Turetzky
6,531,982	B1	3/2003	White
6,538,757	B1	3/2003	Sansone
6,539,200	B1	3/2003	Schiff
6,539,304	B1	3/2003	Chansarkar
6,542,464	B1	4/2003	Takeda
6,542,734	B1	4/2003	Abrol
6,542,743	B1	4/2003	Soliman
6,549,776	B1	4/2003	Joong
6,549,844	B1	4/2003	Egberts
6,556,832	B1	4/2003	Soliman
6,560,461	B1	5/2003	Fomukong
6,560,534	B2	5/2003	Abraham
6,567,035	B1	5/2003	Elliott
6,570,530	B2	5/2003	Gaal
6,574,558	B2	6/2003	Kohli
6,580,390	B1	6/2003	Hay
6,584,552	B1	6/2003	Kuno
6,594,500	B2	7/2003	Bender
6,597,311	B2	7/2003	Sheynblat

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,603,973 B1 8/2003 Foladare
6,606,495 B1 8/2003 Korpi
6,606,554 B2 8/2003 Edge
6,609,004 B1 8/2003 Morse
6,611,757 B2 8/2003 Brodie
6,618,670 B1 9/2003 Chansarkar
6,621,452 B2 9/2003 Knockheart
6,628,233 B2 9/2003 Knockheart
6,633,255 B2 10/2003 Krasner
6,640,184 B1 10/2003 Rabe
6,650,288 B1 11/2003 Seitz
6,661,372 B1 12/2003 Girerd
6,665,539 B2 12/2003 Sih
6,665,541 B1 12/2003 Krasner
6,671,620 B1 12/2003 Garin
6,677,894 B2 1/2004 Sheynblat
6,680,694 B1 1/2004 Knockheart
6,680,695 B2 1/2004 Turetzky
6,691,019 B2 2/2004 Seeley
6,694,258 B2 2/2004 Johnson
6,697,629 B1 2/2004 Grilli
6,698,195 B1 3/2004 Hellinger
6,701,144 B2 3/2004 Kirbas
6,703,971 B2 3/2004 Pande
6,703,972 B2 3/2004 van Diggelen
6,704,651 B2 3/2004 Van Diggelen
6,707,421 B1 3/2004 Drury
6,714,793 B1 3/2004 Carey
6,721,871 B2 4/2004 Piispanen
6,724,342 B2 4/2004 Bloebaum
6,725,159 B2 4/2004 Krasner
6,731,940 B1 5/2004 Nagendran
6,734,821 B2 5/2004 Van Diggelen
6,738,013 B2 5/2004 Orler
6,738,800 B1 5/2004 Aquilon
6,741,842 B2 5/2004 Goldberg
6,745,038 B2 6/2004 Callaway, Jr.
6,747,596 B2 6/2004 Orler
6,748,195 B1 6/2004 Phillips
6,751,464 B1 6/2004 Burg
6,756,938 B2 6/2004 Zhao
6,757,544 B2 6/2004 Rangarajan
6,772,340 B1 8/2004 Peinado
6,775,655 B1 8/2004 Peinado
6,775,802 B2 8/2004 Gaal
6,778,136 B2 8/2004 Gronomeyer
6,778,885 B2 8/2004 Agashe
6,781,963 B2 8/2004 Crockett
6,788,249 B1 9/2004 Farmer
6,795,699 B1 9/2004 McCraw
6,799,050 B1 9/2004 Krasner
6,801,124 B2 10/2004 Naitou
6,801,159 B2 10/2004 Swope
6,804,524 B1 10/2004 Vandermaijden
6,807,534 B1 10/2004 Erickson
6,810,323 B1 10/2004 Bullock
6,813,560 B2 11/2004 van Diggelen
6,816,111 B2 11/2004 Krasner
6,816,710 B2 11/2004 Krasner
6,816,719 B1 11/2004 Heinonen
6,816,734 B2 11/2004 Wong
6,820,269 B2 11/2004 Kogan
6,829,475 B1 12/2004 Lee
6,832,373 B2 12/2004 O'Neill
6,833,785 B2 12/2004 Brown
6,839,020 B2 1/2005 Geier
6,839,021 B2 1/2005 Sheynblat
6,842,715 B1 1/2005 Gaal
6,853,849 B1 2/2005 Tognazzini
6,853,916 B2 2/2005 Fuchs
6,856,282 B2 2/2005 Mauro
6,861,980 B1 3/2005 Rowitch
6,865,171 B1 3/2005 Nilsson
6,865,395 B2 3/2005 Riley
6,867,734 B2 3/2005 Voor
6,873,854 B2 3/2005 Crockett
6,885,940 B2 4/2005 Brodie
6,888,497 B2 5/2005 King
6,888,932 B2 5/2005 Snip
6,895,238 B2 5/2005 Newell
6,895,249 B2 5/2005 Gaal
6,895,324 B2 5/2005 Straub
6,900,758 B1 5/2005 Mann
6,903,684 B1 6/2005 Simic
6,904,029 B2 6/2005 Fors
6,907,224 B2 6/2005 Younis
6,907,238 B2 6/2005 Leung
6,912,395 B2 6/2005 Benes
6,915,208 B2 7/2005 Garin
6,917,331 B2 7/2005 Gronemeyer
6,930,634 B2 8/2005 Peng
6,937,187 B2 8/2005 Van Diggelen
6,937,872 B2 8/2005 Krasner
6,941,144 B2 9/2005 Stein
6,944,540 B2 9/2005 King
6,947,772 B2 9/2005 Minear
6,950,058 B1 9/2005 Davis
6,956,467 B1 10/2005 Mercado, Jr.
6,957,073 B2 10/2005 Bye
6,961,562 B2 11/2005 Ross
6,965,754 B2 11/2005 King
6,965,767 B2 11/2005 Maggenti
6,970,917 B1 11/2005 Kushwaha
6,973,166 B1 12/2005 Tsumpes
6,973,320 B2 12/2005 Brown
6,975,266 B2 12/2005 Abraham
6,978,453 B2 12/2005 Rao
6,980,816 B2 12/2005 Rohles
6,985,105 B1 1/2006 Seitz
6,996,720 B1 2/2006 DeMello
6,998,985 B2 2/2006 Reisman
6,999,782 B2 2/2006 Shaughnessy
7,020,440 B2 * 3/2006 Watanabe et al. 455/67.11
7,024,321 B1 4/2006 Deniger
7,024,393 B1 4/2006 Peinado
7,047,411 B1 5/2006 DeMello
7,064,656 B2 6/2006 Bekcher
7,065,351 B2 6/2006 Carter
7,065,507 B2 6/2006 Mohammed
7,071,814 B1 7/2006 Schorman
7,079,857 B2 7/2006 Maggenti
7,103,018 B1 9/2006 Hasen
7,103,574 B1 9/2006 Peinado
7,106,717 B2 9/2006 Rosseau
7,136,838 B1 11/2006 Peinado
7,151,946 B2 12/2006 Magennti
7,177,623 B2 2/2007 Baldwin
7,203,752 B2 4/2007 Rice
7,209,969 B2 4/2007 Lahti
7,218,940 B2 5/2007 Niemenna
7,221,959 B2 5/2007 Lindqvist
7,269,413 B2 9/2007 Kraft
7,301,494 B2 11/2007 Waters
7,324,823 B1 1/2008 Rosen
RE42,927 E 11/2011 Want
8,190,169 B2 5/2012 Shim
8,314,683 B2 11/2012 Pfeffer
8,442,807 B2 5/2013 Ramachandran
2001/0011247 A1 8/2001 O'Flaherty
2002/0037735 A1 3/2002 Maggenti
2002/0052214 A1 5/2002 Maggenti
2002/0061760 A1 5/2002 Maggenti
2002/0069529 A1 6/2002 Wieres
2002/0102999 A1 8/2002 Maggenti
2002/0112047 A1 8/2002 Kushwaha
2002/0135504 A1 9/2002 Singer
2002/0173317 A1 11/2002 Nykanen
2002/0198632 A1 12/2002 Breed
2003/0009602 A1 1/2003 Jacobs
2003/0037163 A1 2/2003 Kitada
2003/0065788 A1 4/2003 Salomaki
2003/0078064 A1 4/2003 Chan
2003/0081557 A1 5/2003 Mettala
2003/0101329 A1 5/2003 Lahti

(56) **References Cited**

U.S. PATENT DOCUMENTS

2003/0101341	A1	5/2003	Kettler
2003/0103484	A1	6/2003	Oommen
2003/0112941	A1	6/2003	Brown
2003/0114157	A1	6/2003	Spitz
2003/0119528	A1	6/2003	Pew
2003/0131023	A1	7/2003	Bassett
2003/0153340	A1	8/2003	Crockett
2003/0153341	A1	8/2003	Crockett
2003/0153342	A1	8/2003	Crockett
2003/0153343	A1	8/2003	Crockett
2003/0161298	A1	8/2003	Bergman
2003/0204640	A1	10/2003	Sahinoja
2003/0223381	A1	12/2003	Schroderus
2004/0002326	A1	1/2004	Maher
2004/0044623	A1	3/2004	Wake
2004/0046667	A1	3/2004	Copley
2004/0064550	A1	4/2004	Sakata
2004/0068724	A1	4/2004	Gardner
2004/0090121	A1	5/2004	Simonds
2004/0204806	A1	10/2004	Chen
2004/0205151	A1	10/2004	Sprigg
2004/0229632	A1	11/2004	Flynn
2004/0257273	A1	12/2004	Benco
2005/0003797	A1	1/2005	Baldwin
2005/0028034	A1	2/2005	Gantman
2005/0039178	A1	2/2005	Marolia
2005/0041578	A1	2/2005	Huotari
2005/0086340	A1	4/2005	Kang
2005/0086467	A1	4/2005	Asokan
2005/0112030	A1	5/2005	Gauss
2005/0136895	A1	6/2005	Thenthiruperai
2005/0170856	A1	8/2005	Keyani
2005/0172217	A1	8/2005	Leung
2005/0174987	A1	8/2005	Raghav
2005/0209995	A1	9/2005	Aksu
2005/0233735	A1	10/2005	Karaoguz
2005/0246217	A1	11/2005	Horn
2005/0259675	A1	11/2005	Tuohino
2006/0053225	A1	3/2006	Poikselka
2006/0058045	A1	3/2006	Nilsen
2006/0073810	A1	4/2006	Pyhalammi
2006/0074618	A1	4/2006	Miller
2006/0090136	A1	4/2006	Miller
2006/0097866	A1	5/2006	Adamczyk
2006/0212558	A1	9/2006	Sahinoja
2006/0212562	A1	9/2006	Kushwaha
2006/0234639	A1	10/2006	Kushwaha
2006/0234698	A1	10/2006	Folk
2006/0246920	A1	11/2006	Shim
2007/0026854	A1	2/2007	Nath
2007/0030116	A1	2/2007	Feher
2007/0030539	A1	2/2007	Nath
2007/0030973	A1	2/2007	Mikan
2007/0049287	A1	3/2007	Dunn
2007/0186105	A1	8/2007	Bailey
2007/0191025	A1	8/2007	McBrierty
2007/0271596	A1	11/2007	Boubion
2008/0026723	A1	1/2008	Han
2008/0160980	A1	7/2008	Harris
2008/0198989	A1	8/2008	Contractor
2008/0318591	A1	12/2008	Oliver
2009/0058830	A1	3/2009	Herz
2009/0140851	A1	6/2009	Graves
2009/0204815	A1	8/2009	Dennis
2009/0222388	A1	9/2009	Hua
2009/0271486	A1	10/2009	Ligh
2009/0311992	A1	12/2009	Jagetiya
2009/0328135	A1	12/2009	Szabo
2010/0024045	A1	1/2010	Sastry
2010/0050251	A1	2/2010	Speyer
2010/0197318	A1 *	8/2010	Petersen et al. 455/456.1
2010/0205542	A1	8/2010	Walman
2010/0285763	A1	11/2010	Ingrassia
2010/0285814	A1	11/2010	Price
2010/0308993	A1	12/2010	Ma

OTHER PUBLICATIONS

International Preliminary Report on Patentability received in PCT/US2012/00374 dated Sep. 5, 2013.
Internal Search Report received in PCT/US2009/ 05575 dated Jan. 14, 2011.
Internal Search Report received in PCT/US2009/05575 dated Dec. 3, 2009.
International Search Report received in PCT/US2011/01198 dated Aug. 6, 2012.
Internal Search Report received in PCT/US2011/000671 dated Jul. 27, 2011.
Internal Search Report received in PCT/US2011/000671 dated Apr. 25, 2012.
International Search Report in PCT/US2010/001134 dated Oct. 31, 2011.
Internal Search Report received in PCT/US2011/00950 dated Sep. 16, 2011.
International Search Report in PCT/US2011/00950 dated Apr. 30, 2012.

* cited by examiner

FIG. 1


316
INTERNET
LOCATION BASED SERVICES (LBS)
318
400
AGGREGATE LOCATION DYNOMETER (ALD)
302
304
306
NETWORK MONITOR
CROWD RISK DETERMINANT
ALERT MODULE
322
320
WIRELESS CARRIER NETWORK
PUBLIC SAFETY PERSONNEL
324
ACCEPTABLE / NON-ACCEPTABLE CROWD SHAPE DB
CONFIGURABLE PARAMETER THRESHOLD DB
HISTORICAL WIRELESS DEVICE LOCATION TRENDS AND STATISTICS DB
RISK RULES DB
308
310
312
314

FIG. 2


NETWORK MONITOR 302
MONITOR TRAFFIC
500
COMPARE TRAFFIC PARAMETERS WITH CONFIGURABLE PARAMETER THRESHOLD DB
510
302
520
VIRAL EVENT OCCURING?
YES
TO CROWD RISK DETERMINANT 304
NO
LOG LOCATION DATA IN HISTORICAL WIRELESS DEVICE LOCATION TRENDS AND STATISTICS DB
530

FIG. 3


CROWD RISK DETERMINANT 304
FROM NETWORK MONITOR 302
INITIATE LOCATION PUSH/PULL
540
COMPARE VIRAL PATTERN WITH PARAMETERS STORED IN RISK RULES DB
550
304
560
PUBLIC SAFETY RISK?
YES
TO ALERT MODULE 306
NO
LOG LOCATION DATA IN HISTORICAL WIRELESS DEVICE LOCATION TRENDS AND STATISTICS DB
530

FIG. 4


ALERT MODULE 306
FROM CROWD RISK DETERMINANT 304
PUBLIC SAFETY RISK LOGISTICS
700
710
ALERT AUTHORITIES
320
PUBLIC SAFETY PERSONNEL
306
IS PUBLIC SAFETY EVENT PROGRAMMED TO REQUIRE ADDITIONAL LOCATION INFORMATION?
720
YES
NO
540
INITIATE LOCATION PUSH / PULL
530
LOG LOCATION DATA IN HISTORICAL WIRELESS DEVICE LOCATION TRENDS AND STATISTICS DB
730
END



FIG. 5



FIG. 6

FIG. 7

AGGREGATE LOCATION DYNOMETER (ALD)

The present application is a continuation of U.S. application Ser. No. 13/317,996 entitled "Aggregate Location Dynometer (ALD)", filed on Nov. 2, 2011, now U.S. Pat. No. 8,649,806; which claims priority from U.S. Provisional Application No. 61/573,112, entitled "Aggregate Location Dynometer (ALD)", filed Sep. 2, 2011, the entirety of both of which are expressly incorporated herein by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention relates generally to wireless telecommunications. More particularly, it relates to cell location services, cell network trafficking and analysis of location information.

2. Background of Related Art

Location based applications obtain a geographic position of a particular wireless device and provide services accordingly. Location based services (LBS) prevail in today's market due to an incorporation of tracking technology in handheld devices.

Location based pull services allow a wireless device user to locate another wireless device. Current location services are generally focused on individual wireless device user applications.

SUMMARY OF THE INVENTION

In accordance with the principles of the present invention, a method of alerting to a problematic crowd risk in a given geographical location, comprises an Aggregate Location Dynometer (ALD). The Aggregate Location Dynometer (ALD) utilizes location based services (LBS) to analyze aggregate location information pertaining to a multitude of wireless devices, to detect potential crowd risks.

An Aggregate Location Dynometer (ALD) resides in a physical network server, in accordance with the present invention, and comprises three main components: a Network Monitor, a Crowd Risk Determinant, and an Alert Module.

The Network Monitor monitors a wireless network for indication of a possible impending viral event, in accordance with the principles of the present invention. In particular, the Network Monitor utilizes location based services (LBS) to monitor the formation of a plurality of wireless devices at a given point in a wireless network, e.g., a given base station (BS). The Network Monitor compares obtained traffic parameters pertaining to monitored wireless traffic, with historical traffic parameters having to do with crowd risk determination, to determine if a viral event may be occurring or impending. A snapshot look at current location data collected by the Network Monitor is subsequently logged in an appropriate historical database.

In accordance with the principles of the present invention, the Crowd Risk Determinant analyzes location information to determine if a viral event triggered by the Network Monitor, also indicates a crowd safety risk. In particular, the Crowd Risk Determinant initiates a location request to obtain location information pertaining to a multitude of wireless devices in a given area, regarding a viral event that has been triggered by the Network Monitor. The Crowd Risk Determinant compares the viral pattern formed by the shape and movement of wireless devices in locations observed, with predetermined risk rules to determine if the viral event is also a crowd safety risk. The observed viral pattern is subsequently logged in an appropriate historical database.

The Alert Module, in accordance with the principles of the present invention, alerts proper authorities in an event of a crowd safety risk. The Crowd Risk Determinant triggers the Alert Module to alert of an impending crowd problem when crowd risk has exceeded a given threshold.

The Aggregate Location Dynometer (ALD) utilizes historical databases, in accordance with the present invention, to maintain location-based information indicating possible viral events associated with a plurality of wireless devices. Historical databases include an Acceptable/Non-Acceptable Crowd Shape database, a Configurable Parameter Threshold database, a Historical Wireless Device Location Trends database, and a Risk Rules database.

BRIEF DESCRIPTION OF THE DRAWINGS

Features and advantages of the present invention will become apparent to those skilled in the art from the following description with reference to the drawings, in which:

FIG. **1** depicts an exemplary Aggregate Location Dynometer (ALD), in accordance with the principles of the present invention.

FIG. **2** depicts the flow of an exemplary Network Monitor of the Aggregate Location Dynometer (ALD), in accordance with the principles of the present invention.

FIG. **3** depicts the flow of an exemplary Crowd Risk Determinant of the Aggregate Location Dynometer (ALD), in accordance with the principles of the present invention.

FIG. **4** depicts the flow of an exemplary Alert Module of the Aggregate Location Dynometer (ALD), in accordance with the principles of the present invention.

FIG. **5** denotes first exemplary Aggregate Location Dynometer (ALD) location results, in accordance with the principles of the present invention.

FIG. **6** denotes second exemplary Aggregate Location Dynometer (ALD) location results, in accordance with the principles of the present invention.

FIG. **7** denotes third exemplary Aggregate Location Dynometer (ALD) location results, in accordance with the principles of the present invention.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

Thus far, location capabilities have been concerned with locating an individual wireless device. Yet, there is such a vast abundance of individuals populating the nation's major cities. The present inventor has appreciated the benefits of using location based services (LBS) to obtain sets of aggregate location data corresponding to a number and pattern of wireless devices within an area, region, city, etc. of interest.

The present invention introduces an Aggregate Location Dynometer (ALD), an analytical server utilizing location based services (LBS) on a network to predict public safety risks, e.g., the unexpected impending formation of a flash mob, or a riot, etc.

The Aggregate Location Dynometer (ALD) analyzes a bird's-eye view of people formation, presuming those individuals possess respective handheld wireless devices that permit collection of current location information, whether that current location information be obtained from the wireless devices themselves, and/or from a network-based location server.

In accordance with the principles of the present invention, the Aggregate Location Dynometer (ALD) predicts public safety risk in a given geographical area through evaluation of the positioning and movement of wireless devices. The

Aggregate Location Dynometer (ALD) monitors wireless device network traffic to predict an impending viral event. If a possible impending viral event is sensed from a general monitoring of wireless traffic, the Aggregate Location Dynometer (ALD) may request impending viral location information pertaining to clusters of wireless devices in a vicinity of the possible event, to more accurately assess crowd risk.

Crowd risk is assessed based upon given wireless network traffic parameters such as the number of wireless devices in communication with a given base station (e.g., a density), the shape formed by representations of the individual locations of the densest areas where active wireless devices are currently located, and/or the movement of the wireless devices within the region as defined.

Markers, each representing a wireless device at a given location at a given time, may be displayed on a display of the Aggregate Location Dynometer (ALD). The markers may represent wireless devices served within the given region, whether actively communicating with another wireless device, or merely sensed as present.

The present invention preferably provides an alert of a possible impending crowd related public safety risk in real time, as the crowd risk arises, informing emergency personnel as early as possible, even before such event is consummated.

FIG. **1** depicts an exemplary Aggregate Location Dynometer (ALD) **400**, in accordance with the principles of the present invention.

In particular, an Aggregate Location Dynometer (ALD) **400** determines crowd safety risk with the help of location based services (LBS) **318**, as depicted in FIG. **1**.

The Aggregate Location Dynometer (ALD) **400** is generally based in a server in a wireless network **322**. Three main components form the Aggregate Location Dynometer (ALD) **400**: a Network Monitor **302**, a Crowd Risk Determinant **304**, and an Alert Module **306**.

The Network Monitor **302** begins the risk determination process of the Aggregate Location Dynometer (ALD) **400** by monitoring the network for indication of a possible viral event, in accordance with the principles of the present invention. Determination of a viral event is the first step in the escalation-based response of the Aggregate Location Dynometer (ALD) **400**.

The Crowd Risk Determinant **304** assesses location information pertaining to a possible viral event triggered by the Network Monitor **302**. The Crowd Risk Determinant **304** determines if a viral event also indicates a public safety risk.

The Alert Module **306** performs predetermined responsive measures to alert appropriate public safety personnel **320** in the event of a possible or probable or current public safety risk.

Historical databases are empirically determined and maintained in the Aggregate Location Dynometer (ALD) **400** for use in crowd risk assessment. The historical databases preferably store sets of aggregate current location information pertaining to trackable wireless devices. Exemplary historical databases accessible by the Aggregate Location Dynometer (ALD) **400** include but are not limited to a Historical Wireless Device Location Trends and Statistics database **312**, a Configurable Parameter Threshold database **310**, a Risk Rules database **314**, and an Acceptable/Non-Acceptable Crowd Shape database **308**.

The Historical Wireless Device Location Trends and Statistics database **312**, as shown in FIG. **1**, preferably stores sets of instantaneous aggregate location information obtained over a period of time. Data stored in the Historical Wireless Device Location Trends and Statistics database **312** provides empirical evaluation of crowd activities used to detect a crowd trend. The Aggregate Location Dynometer (ALD) **400** preferably uses data stored in the Historical Wireless Device Location Trends and Statistics database **312** to determine if a current situation is considered to be 'normal' to the monitored area, or abnormal, triggering a viral event. The data maintained in the Historical Wireless Device Location Trends and Statistics database **312** is preferably refreshed over time.

The Configurable Parameter Threshold database **310**, as depicted in FIG. **1**, preferably comprises a set of configurable location-based parameters and thresholds including density, clustering, spread, geographical boundary, motion trends, and/or special events occurring in particular areas. The Configurable Parameter Threshold database **310** can also include non-location based parameters such as time of day and/or message content. The parameters stored in the Configurable Parameter Threshold database **310** are accessed by the Network Monitor **302** to assist in detecting a viral event.

The Risk Rules database **314**, as shown in FIG. **1**, preferably comprises a set of configurable location-based parameters and thresholds including density, clustering, spread, geographical boundary, motion trends, and/or special events occurring in particular areas. The Risk Rules database **314** can also include non-location based parameters such as time of day and/or message content. The parameters stored in the Risk Rules database **314** are accessed by the Crowd Risk Determinant **304** to assist in determining if a viral event also indicates a public safety risk.

The Acceptable/Non-Acceptable Crowd Shape database **308**, as shown in FIG. **1**, holds empirically determined past, historical cluster information regarding acceptable and/or non-acceptable past shape formations of clustered wireless devices. Specific shape parameters stored in the Acceptable/Non-Acceptable Crowd Shape database **308** are accessed by the Crowd Risk Determinant **304** to assist in determining if a viral event also indicates a public safety risk.

A viral event is the first state of alarm in the multi-state risk determination process of the Aggregate Location Dynometer (ALD) **400**. A viral event is defined as occurring when one or more predefined parameter thresholds have been surpassed, as determined in the exemplary embodiment in the Network Monitor **302**. The occurrence of a viral event does not necessarily infer a definite public safety risk. Instead, a viral event triggers the Crowd Risk Determinant **304** to further analyze a potentially malignant event more closely. For example, the Crowd Risk Determinant **304** provides a closer inspection of aggregate current location information, e.g., via use of a location-based push/pull service. A match of more detailed location information to a historical pattern leading to crowd risk may determine that a particular viral event also indicates a likely public safety risk.

A public safety risk confirms a compromise in crowd safety, e.g., the impending formation of a flash mob, or a riot, etc. Determination of a public safety risk triggers the Alert Module **306** to implement proper public safety response services.

The Network Monitor **302** begins the risk determination process of the Aggregate Location Dynometer (ALD) **400**, by monitoring the network for indication of a possible viral event, in accordance with the principles of the present invention.

Moreover, the Network Monitor **302** retrieves subsequent sets of instantaneous aggregate location information. Location information triggered by the Network Monitor **302** may be portrayed in the form of snapshots displayed on a display of the Aggregate Location Dynometer (ALD) **400**. Snapshots

by the Network Monitor **302** comprise markers, each representing the location of individual wireless devices within a given region being monitored.

The Network Monitor **302** preferably obtains information regarding the number of wireless devices in a geographical area, at a given time, supported by a particular wireless network carrier (e.g., the number of wireless devices sending messages over a wireless network via a particular base station (BS) **324**). The Network Monitor **302** uses predefined parameters and thresholds to determine if the monitored network indicates that a viral event may be occurring or impending (e.g., surpassed parameter thresholds possibly indicative of an excessive number and/or use of wireless devices for a given area, cell tower, etc.).

For instance, a Maximum Number of Devices parameter may indicate the maximum number of wireless devices that may be present within range of a particular base station (BS) **324** at a given time before a possible viral event is triggered. The Maximum Number of Devices parameter may be set manually, or empirically determined (e.g., the average number of devices present at a particular base station (BS) **324** over a course of time, as determined by historical data stored in the Historical Wireless Device Location Trends and Statistics database **312**).

The Network Monitor **302** triggers a possible viral event if a predefined parameter threshold has been surpassed (e.g., a given density of current location markers each representing a separate wireless device, or a directed convergence of at least two highly dense clusters of markers toward each other at a significant rate of speed is or has occurred, etc.).

The Network Monitor **302** preferably tallies the number of wireless devices in each instantaneous aggregate location snapshot that is captured. Predetermined parameters and thresholds are used to assess the number (e.g., the density) of wireless devices in a particular area to determine whether or not a possible viral event is occurring.

The Maximum Number of Devices parameter may alternatively be set to indicate the maximum number of wireless devices that may be present in an instantaneous aggregate location snapshot before a possible viral event is triggered. If the number of devices present in a given snapshot exceeds the Maximum Value of Devices parameter established for the respective location, a viral event may be triggered.

The Network Monitor **302** also preferably tallies the difference in the number of wireless devices in a given area, from one consecutive instantaneous aggregate location snapshot to the next. If the difference in the number of wireless devices from snapshot to snapshot exceeds a predefined value in a number of consecutive snapshots for a given area, base station, etc., then a viral event may be triggered. Thresholds for such a predefined Maximum Difference in Number of Wireless Devices parameter and a predefined Interval of Consecutive Snapshots parameter may be set manually, or empirically determined (e.g., the average difference in number of devices in consecutive instantaneous aggregate location snapshots capturing a particular area, e.g., a number of square feet, a particular base station (BS), etc., over a course of time, supported by a particular network carrier, as recorded in the Historical Wireless Device Location Trends and Statistics database **312**).

FIG. **2** depicts the flow of an exemplary Network Monitor **302** of the Aggregate Location Dynometer (ALD) **400**, in accordance with the principles of the present invention.

In particular, as shown in step **500** of FIG. **2**, the Network Monitor **302** preferably continuously, or at least periodically or intermittently, monitors network traffic.

In step **510**, monitored wireless data traffic is inspected for the presence of abnormal events, e.g., excessive volume for the time of day, etc. Configurable thresholds for the monitored parameters may be dynamic over the course of the day and even for traffic for any given tower or base station. The configurable thresholds for monitored parameters may be stored in the Configurable Parameter Threshold database **310**.

As shown in step **520**, if one or more parameter thresholds are exceeded, a viral event may be triggered. In response, the Network Monitor **302** triggers the Crowd Risk Determinant **304** to perform a location-based push/pull service to determine the location of each trackable wireless device within a particular geographic area (e.g., communicating through given base stations or antennas).

When parameter thresholds are not surpassed, indicating that a viral event is not occurring, location data may be logged in the Historical Wireless Device Location Trends and Statistics database **312**, as depicted in step **530**. Location data logged in the Historical Wireless Device Location Trends and Statistics database **312** may be used by the Crowd Risk Determinant **304** for future analyses of crowd risk.

FIG. **3** depicts the flow of an exemplary Crowd Risk Determinant **304** of the Aggregate Location Dynometer (ALD) **400**, in accordance with the principles of the present invention.

In particular, the Crowd Risk Determinant **304** performs a location-based push/pull service to obtain location information pertaining to trackable wireless devices in a given area regarding a respective viral event triggered by the Network Monitor **302**, as shown in step **540** of FIG. **3**.

In step **550**, collected location data is analyzed to assess the viral event that is occurring. The Crowd Risk Determinant **304** uses bounds and priorities set forth in the Risk Rules database **314** to determine if a possible viral event indicates a public safety risk. A viral pattern may or may not imply public safety risk. In step **560**, if a public safety risk is determined, the Crowd Risk Determinant **304** triggers the Alert Module **306** to take responsive public safety measures. Location data associated with a public safety risk is logged **530** in the Historical Wireless Device Location Trends and Statistics database **312**.

If the Crowd Risk Determinant **304** confirms that a particular viral event does not indicate a public safety risk, the Aggregate Location Dynometer (ALD) **400** is triggered to routinely log location data **530** in the Historical Wireless Device Location Trends and Statistics database **312** for potential future analyses.

Determination of a public safety risk in the Crowd Risk Determinant **304** triggers the Alert Module **306** to implement proper public safety response services. An Alert Module **306** is the final step in the risk determination process of the Aggregate Location Dynometer (ALD) **400**.

FIG. **4** depicts the flow of an exemplary Alert Module **306** of the Aggregate Location Dynometer (ALD) **400**, in accordance with the principles of the present invention.

In particular, as shown in step **700** of FIG. **4**, the Alert Module **306** is triggered by the Crowd Risk Determinant **304** and supplied the predetermined conditions constituting how to handle a determined public safety risk.

The Alert Module **306** immediately alerts the proper authorities **320** in the presence of a public safety risk, as depicted in step **710**.

Subsequent aggregate data collections may be made by the Alert Module **306** in step **720**. A particular public safety event may be programmed to result in multiple aggregate location data collections, set to occur at specific intervals. Moreover, a particular risk determination result may be configured to act

as a triggered push/pull service **540** to acquire additional location data. Subsequent location information is routinely logged in the Historical Wireless Devices Location Trends and Statistics database **530**.

Configurable parameters are maintained in the Risk Rules database **314** to assist the Crowd Risk Determinant **304** in determining if location information pertaining to a viral event indicates a likely public safety risk. Factors for risk determination include but are not limited to the shape a cluster of location markers representing individual wireless devices of given density is forming, whether or not markers are spreading out or coming together, and/or at what rate of change a cluster of wireless devices is moving. Factors for risk determination also include the behavior of collective XY location coordinates of the most dense clusters of wireless devices, to where the most dense clusters of wireless devices of concern are moving, and/or whether or not a cluster of wireless devices in a particular location makes sense given the time of day.

For instance, empirical data may indicate that it is unusual for there to be a large number of wireless devices present downtown after business hours, or after a time when local bars and clubs have closed for the night. In this case, a configurable threshold may be set for a combination of location and time of day parameters (e.g., to articulate the number of wireless devices that must be present within a defined downtown region, after a given hour) to trigger a public safety risk. A configurable parameter threshold (e.g., specifying the number of wireless devices capable of inhabiting a particular geographic expanse or particular shape of device formation, or a given density within that region) may manually or empirically be set. If a parameter threshold is surpassed, the Crowd Risk Determinant **304** informs the Alert Module **306** of the development of a public safety risk.

The shape of a cluster of wireless devices may often offer significant clues to crowd risk potential. When location information is collected, the best-fit shape of dense clusters formed by accumulation of wireless devices in a given area may be determined. The best-fit shape of a cluster of wireless devices may be compared against data contained in the historical Acceptable/Non-Acceptable Crowd Shape database **308** to determine danger potential. Different thresholds may be set for like parameters based on varying location.

FIG. **5** denotes first exemplary Aggregate Location Dynometer (ALD) **400** location results, in accordance with the principles of the present invention.

In particular, the large oval shape **101** formed by markers representing individual wireless devices in the given geographical area **200** shown in FIG. **5**, may be interpreted as a group of individuals enjoying a sporting event in a stadium. Factors to consider are time of day and scheduled events. The example in FIG. **5** uses precise location.

FIG. **6** denotes second exemplary Aggregate Location Dynometer (ALD) **400** location results, in accordance with the principles of the present invention.

In particular, the pattern **102** in the geographical area **200** shown in FIG. **6** may be interpreted as cell sites pertaining to trackable individuals, assuming most individuals carry wireless devices. The same pattern may mean different things at different hours of the day. The exemplary location result shown in FIG. **6** uses coarse location.

FIG. **7** denotes third exemplary Aggregate Location Dynometer (ALD) **400** location results, in accordance with the principles of the present invention.

In particular, the crescent shape **103** in the geographical area **200** shown in FIG. **7** is recognized as a pattern to be wary of. This crescent shape may represent a variety of different occurrences (e.g., a protest in front of a given location such as a court house, a famous author at a bookstore, etc.). The exemplary location result shown in FIG. **7** uses precise location.

A rate-based parameter threshold may also or alternatively be set to define an acceptable rate at which wireless devices would otherwise normally inhabit a geographic area. For instance, if over a certain number of wireless devices enter an area in under a given amount of time (e.g., if three hundred wireless devices rush into a central pre-defined location in under ten minutes) then a public safety risk may be triggered.

Message content may be analyzed as an attribute for risk determination in response to a viral traffic event. For instance, a determination of the most frequent phrases may be matched against a database of suspected terms (e.g., "meet at the Lincoln Memorial", etc.).

Motion trends are also analyzed to assess crowd risk. The Crowd Risk Determinant **304** preferably determines whether the accumulation of wireless devices is becoming more or less dense about a central location and whether or not this behavior is expected based on trends and configured thresholds established for particular locations.

Precise accuracy of each individual device location is not extremely important in the present invention. Instead, focus lies in the volume, density, shape and movement of data points collected. Serving cell tower locations for each wireless device may be sufficient to satisfy initial triggering requirements for a possible viral event. The Aggregate Location Dynometer (ALD) **400** is concerned with aggregate location data as opposed to data involving individual device locations. Data regarding parameters such as special events, geographical boundaries, motion trends, density, clustering, spread, time of day and/or message content relating to trackable wireless devices are recorded in the Historical Wireless Device Location Trends and Statistics database **312**, as opposed to exact locations of specific wireless devices. Anonymity regarding precise locations of specific wireless devices alleviates some concern surrounding the privacy of individuals during location based services (LBS), as used within the present invention.

An Aggregate Location Dynometer (ALD) **400** has benefit to entities other than emergency management and crowd risk assessment parties. For instance, the present invention may also be used to estimate location trends in cities, to rank areas such as parks and beaches by volume of visitors, and even to peg traffic patterns. Historical crowd data need not represent a public safety issue, e.g., it may merely relate to city planning or disaster recovery. Thus, data collected while scanning for crowd risk provides cities, states and government with valuable information.

Though, preferably all wireless devices in a given area would be monitored for crowd gathering tendencies, it is also within the principles of the present invention to monitor only those devices by the relevant wireless carrier providing Location Dynometer (ALD) **400** services.

The present invention greatly benefits police, fire and general emergency response personnel **320** desiring early warning about possible crowd related risks, e.g., riots. Moreover, the present invention is intended to combat nefarious cell technology to spawn mobs and riots without resorting to network restrictions.

While the invention makes use of the current location data of preferably all wireless devices within a given region, area, etc., the invention also preferably makes distinction between the current mode of operation of the wireless devices being analyzed for a possible public safety risk. For instance, analy-

sis of the density, shape, movement, etc. in determining a possible public safety risk may analyze only wireless devices in active mode.

While the invention has been described with reference to the exemplary embodiments thereof, those skilled in the art will be able to make various modifications to the described embodiments of the invention without departing from the true spirit and scope of the invention.

What is claimed is:

1. An aggregate location dynometer in a physical wireless network server, said aggregate location dynometer comprising:

a network monitor to monitor a wireless network for an indication of a viral event;

a location aggregator to obtain a location of each of a plurality of wireless devices associated with said viral event;

a crowd risk determinant, triggered by said network monitor, to determine a crowd risk based on an aggregation of said location of each of said plurality of wireless devices associated with said viral event; and

an alert module to initiate an alert message relating to a public safety risk determined from an analysis of said viral event.

2. The aggregate location dynometer in a physical wireless network server, said aggregate location dynometer according to claim **1**, further comprising:

a historical database maintaining a geographic region associated with said viral event.

3. The aggregate location dynometer in a physical wireless network server, said aggregate location dynometer according to claim **2**, wherein said historical databases comprises:

a plurality of acceptable crowd shapes, a crowd shape being defined by said aggregation of said location of each of said plurality of wireless devices associated with said viral event.

4. The aggregate location dynometer in a physical wireless network server, said aggregate location dynometer according to claim **2**, wherein said historical databases comprises:

a plurality of non-acceptable crowd shapes, a crowd shape being defined by said aggregation of said location of each of said plurality of wireless devices associated with said viral event.

5. The aggregate location dynometer in a physical wireless network server, said aggregate location dynometer according to claim **2**, wherein said historical databases comprises:

a configurable parameter defining a threshold of a crowd shape becoming unacceptable and thus said crowd risk.

6. The aggregate location dynometer in a physical wireless network server, said aggregate location dynometer according to claim **2**, wherein said historical databases comprises:

a plurality of crowd shape trends based on historical wireless device locations during previous viral events.

7. A method of alerting to a problematic crowd risk based on location based services (LBS), comprising:

monitoring wireless traffic for a forming viral event associated with a plurality of physical wireless devices within a given region;

initiating location requests to a physical location server to obtain a current location of each of said plurality of physical wireless devices;

forming a crowd shape based on an aggregation of said current location of each of said plurality of physical wireless devices;

determining a crowd risk of said crowd based on said crowd shape of said current location of each of said plurality of physical wireless devices; and

triggering a crowd alert message when said determined crowd risk is above a given threshold.

8. The method of alerting to a problematic crowd risk with location based services (LBS) according to claim **7**, wherein:

said crowd risk of said crowd is further determined based on a movement of said crowd shape.

9. The method of alerting to a problematic crowd risk with location based services (LBS) according to claim **7**, wherein said monitoring wireless traffic comprises:

monitoring wireless traffic at a given point in a wireless network; and

comparing a given traffic parameter associated with said obtained current location of each of said plurality of physical wireless devices, with a historical traffic parameter associated with a previous problematic crowd formation.

10. The method of alerting to a problematic crowd risk with location based services (LBS) according to claim **9**, wherein:

said given point is at a given base station in said wireless network.

11. The method of alerting to a problematic crowd risk with location based services (LBS) according to claim **9**, further comprising:

logging a snapshot formation created by said current location of each of said plurality of physical wireless devices.

12. The method of alerting to a problematic crowd risk with location based services (LBS) according to claim **7**, wherein said initiating location requests comprises:

initiating a location request for each of said plurality of physical wireless devices.

13. The method of alerting to a problematic crowd risk with location based services (LBS) according to claim **7**, further comprising:

comparing a viral pattern of respective locations of said plurality of wireless devices to predetermined risk rules.

14. The method of alerting to a problematic crowd risk with location based services (LBS) according to claim **13**, further comprising:

logging said viral pattern.

* * * * *

Exhibit B

to

Complaint
for Patent Infringement

The ’158 Patent

US009402158B2

(12) **United States Patent**
Cuff et al.

(10) **Patent No.: US 9,402,158 B2**
(45) **Date of Patent: *Jul. 26, 2016**

(54) **AGGREGATE LOCATION DYNOMETER (ALD)**

(71) Applicant: **TeleCommunication Systems, Inc.**, Annapolis, MD (US)

(72) Inventors: **Michael A. Cuff**, Clyde Hill, WA (US); **Todd Gehrke**, Seattle, WA (US); **Farhad Kasad**, Bothell, WA (US)

(73) Assignee: **Telecommunication Systems, Inc.**, Annapolis, MD (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/885,136**

(22) Filed: **Oct. 16, 2015**

(65) **Prior Publication Data**

US 2016/0044461 A1 Feb. 11, 2016

Related U.S. Application Data

(63) Continuation of application No. 14/176,691, filed on Feb. 10, 2014, now Pat. No. 9,198,054, which is a continuation of application No. 13/317,996, filed on Nov. 2, 2011, now Pat. No. 8,649,806.

(60) Provisional application No. 61/573,112, filed on Sep. 2, 2011.

(51) **Int. Cl.**
H04W 4/00 (2009.01)
H04W 4/02 (2009.01)
(Continued)

(52) **U.S. Cl.**
CPC ***H04W 4/023*** (2013.01); ***H04L 67/22*** (2013.01); ***H04W 4/028*** (2013.01); ***H04W 4/22*** (2013.01); ***H04W 24/00*** (2013.01); ***H04W 24/08*** (2013.01); ***H04W 64/006*** (2013.01)

(58) **Field of Classification Search**
CPC H04W 4/22; H04W 4/02; H04W 4/028; H04W 76/007; H04W 4/023; H04W 64/006; H04W 4/025; H04M 11/04; H04M 2242/04; G06Q 30/0201
USPC 455/414.1, 456.1–456.6, 457, 404.1, 455/404.2
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,445,118 A 4/1984 Taylor
4,928,107 A 5/1990 Kuroda
(Continued)

OTHER PUBLICATIONS

Internal Search Report received in PCT/US2009/05575 dated Jan. 14, 2011.
(Continued)

Primary Examiner — Olumide T Ajibade Akonai
(74) *Attorney, Agent, or Firm* — Tarolli, Sundheim, Covell & Tummino LLP

(57) **ABSTRACT**

An Aggregate Location Dynometer (ALD) in a physical wireless network alerts to a problematic crowd risk using location based services (LBS). An Aggregate Location Dynometer (ALD) comprises a Network Monitor, a Crowd Risk Determinant and an Alert Module. The Network Monitor monitors wireless traffic for a potential viral event, associated with a formation of a plurality of wireless devices. The Crowd Risk Determinant requests location information associated with a plurality of wireless devices in a given area regarding a respective viral event. The Crowd Risk Determinant determines if the viral event also indicates a crowd safety risk, based on the shape and movement of observed wireless devices. The Alert Module triggers an alert of an impending crowd problem when crowd risk is above a given threshold. Historical databases are empirically determined and maintained in the Aggregate Location Dynometer (ALD) for use in viral event and crowd risk assessment.

16 Claims, 7 Drawing Sheets



(51) **Int. Cl.**

H04L 29/08	(2006.01)
H04W 24/08	(2009.01)
H04W 4/22	(2009.01)
H04W 64/00	(2009.01)
H04W 24/00	(2009.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,972,484	A	11/1990	Theile
5,126,722	A	6/1992	Kamis
5,283,570	A	2/1994	DeLuca
5,301,354	A	4/1994	Schwendeman
5,311,516	A	5/1994	Kuznicki
5,327,529	A	7/1994	Fults
5,335,246	A	8/1994	Yokev
5,351,235	A	9/1994	Lahtinen
5,365,451	A	11/1994	Wang
5,418,537	A	5/1995	Bird
5,422,813	A	6/1995	Schuchman
5,479,408	A	12/1995	Will
5,485,163	A	1/1996	Singer
5,504,491	A	4/1996	Chapman
5,506,886	A	4/1996	Maine
5,517,199	A	5/1996	DiMattei
5,530,655	A	6/1996	Lokhoff
5,530,914	A	6/1996	McPheters
5,539,395	A	7/1996	Buss
5,539,829	A	7/1996	Lokhoff
5,546,445	A	8/1996	Dennison
5,568,153	A	10/1996	Beliveau
5,583,774	A	12/1996	Diesel
5,594,780	A	1/1997	Wiedeman
5,606,618	A	2/1997	Lokhoff
5,629,693	A	5/1997	Janky
5,633,630	A	5/1997	Park
5,636,276	A	6/1997	Brugger
5,661,652	A	8/1997	Sprague
5,661,755	A	8/1997	Van de Kerkhof
5,689,245	A	11/1997	Noreen
5,699,053	A	12/1997	Jonsson
5,704,029	A	12/1997	Wright, Jr.
5,721,781	A	2/1998	Deo
5,727,057	A	3/1998	Emery
5,731,785	A	3/1998	Lemelson
5,765,152	A	6/1998	Erickson
5,771,353	A	6/1998	Eggleston
5,774,670	A	6/1998	Montulli
5,809,415	A	9/1998	Rossmann
5,812,086	A	9/1998	Bertiger
5,812,087	A	9/1998	Krasner
5,841,396	A	11/1998	Krasner
5,857,201	A	1/1999	Wright, Jr.
5,864,667	A	1/1999	Barkan
5,874,914	A	2/1999	Krasner
5,896,369	A	4/1999	Warsta
5,922,074	A	7/1999	Richard
5,930,250	A	7/1999	Klok
5,945,944	A	8/1999	Krasner
5,946,629	A	8/1999	Sawyer
5,950,137	A	9/1999	Kim
5,960,362	A	9/1999	Grob
5,983,099	A	11/1999	Yao
5,999,124	A	12/1999	Sheynblat
6,032,051	A	2/2000	Hall
6,049,718	A	4/2000	Stewart
6,052,081	A	4/2000	Krasner
6,058,338	A	5/2000	Agashe
6,061,018	A	5/2000	Sheynblat
6,064,336	A	5/2000	Krasner
6,067,045	A	5/2000	Castelloe
6,081,229	A	6/2000	Soliman
6,085,320	A	7/2000	Kaliski, Jr.
6,118,403	A	9/2000	Lang
6,121,923	A	9/2000	King
6,124,810	A	9/2000	Segal
6,131,067	A	10/2000	Girerd
6,133,874	A	10/2000	Krasner
6,134,483	A	10/2000	Vayanos
6,147,598	A	11/2000	Murphy
6,150,980	A	11/2000	Krasner
6,154,172	A	11/2000	Piccionelli
6,169,901	B1	1/2001	Boucher
6,169,902	B1	1/2001	Kawamoto
6,178,506	B1	1/2001	Quick, Jr.
6,185,427	B1	2/2001	Krasner
6,188,354	B1	2/2001	Soliman
6,188,909	B1	2/2001	Alanara
6,189,098	B1	2/2001	Kaliski, Jr.
6,195,557	B1	2/2001	Havinis
6,204,798	B1	3/2001	Fleming
6,205,330	B1	3/2001	Winbladh
6,208,290	B1	3/2001	Krasner
6,215,441	B1	4/2001	Moeglein
6,239,742	B1	5/2001	Krasner
6,247,135	B1	6/2001	Feague
6,249,873	B1	6/2001	Richard
6,253,203	B1	6/2001	O'Flaherty
6,260,147	B1	7/2001	Quick, Jr.
6,275,692	B1	8/2001	Skog
6,275,849	B1	8/2001	Ludwig
6,297,768	B1	10/2001	Allen, Jr.
6,307,504	B1	10/2001	Sheynblat
6,308,269	B2	10/2001	Proidl
6,313,786	B1	11/2001	Sheynblat
6,321,257	B1	11/2001	Kotola
6,324,542	B1	11/2001	Wright, Jr. et al.
6,327,473	B1	12/2001	Soliman
6,333,919	B2	12/2001	Gaffney
6,360,093	B1	3/2002	Ross
6,360,102	B1	3/2002	Havinis
6,363,254	B1	3/2002	Jones
6,367,019	B1	4/2002	Ansell
6,370,389	B1	4/2002	Isomursu
6,377,209	B1	4/2002	Krasner
6,400,314	B1	6/2002	Krasner
6,400,958	B1	6/2002	Isomursu
6,411,254	B1	6/2002	Moeglein
6,421,002	B2	7/2002	Krasner
6,430,504	B1	8/2002	Gilbert
6,433,734	B1	8/2002	Krasner
6,442,391	B1	8/2002	Johansson
6,449,473	B1	9/2002	Raivisto
6,449,476	B1	9/2002	Hutchison, IV
6,456,852	B2	9/2002	Bar
6,463,272	B1	10/2002	Wallace
6,477,150	B1	11/2002	Maggenti
6,505,049	B1	1/2003	Dorenbosch
6,510,387	B2	1/2003	Fuchs
6,512,922	B1	1/2003	Burg
6,512,930	B2	1/2003	Sandegren
6,515,623	B2	2/2003	Johnson
6,519,466	B2	2/2003	Pande
6,522,682	B1	2/2003	Kohli
6,525,687	B2	2/2003	Roy
6,525,688	B2	2/2003	Chou
6,529,829	B2	3/2003	Turetzky
6,531,982	B1	3/2003	White
6,538,757	B1	3/2003	Sansone
6,539,200	B1	3/2003	Schiff
6,539,304	B1	3/2003	Chansarkar
6,542,464	B1	4/2003	Takeda
6,542,734	B1	4/2003	Abrol
6,542,743	B1	4/2003	Soliman
6,549,776	B1	4/2003	Joong
6,549,844	B1	4/2003	Egberts
6,556,832	B1	4/2003	Soliman
6,560,461	B1	5/2003	Fomukong
6,560,534	B2	5/2003	Abraham
6,567,035	B1	5/2003	Elliott
6,570,530	B2	5/2003	Gaal
6,574,558	B2	6/2003	Kohli
6,580,390	B1	6/2003	Hay
6,584,552	B1	6/2003	Kuno
6,594,500	B2	7/2003	Bender

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,597,311	B2	7/2003	Sheynblat
6,603,973	B1	8/2003	Foladare
6,606,495	B1	8/2003	Korpi
6,606,554	B2	8/2003	Edge
6,609,004	B1	8/2003	Morse
6,611,757	B2	8/2003	Brodie
6,618,670	B1	9/2003	Chansarkar
6,621,452	B2	9/2003	Knockheart
6,628,233	B2	9/2003	Knockheart
6,633,255	B2	10/2003	Krasner
6,640,184	B1	10/2003	Rabe
6,650,288	B1	11/2003	Pitt et al.
6,661,372	B1	12/2003	Girerd
6,665,539	B2	12/2003	Sih
6,665,541	B1	12/2003	Krasner
6,671,620	B1	12/2003	Garin
6,677,894	B2	1/2004	Sheynblat
6,680,694	B1	1/2004	Knockheart
6,680,695	B2	1/2004	Turetzky
6,691,019	B2	2/2004	Seeley
6,694,258	B2	2/2004	Johnson
6,697,629	B1	2/2004	Grilli
6,698,195	B1	3/2004	Hellinger
6,701,144	B2	3/2004	Kirbas
6,703,971	B2	3/2004	Pande
6,703,972	B2	3/2004	van Diggelen
6,704,651	B2	3/2004	van Diggelen
6,707,421	B1	3/2004	Drury
6,714,793	B1	3/2004	Carey
6,721,871	B2	4/2004	Piispanen
6,724,342	B2	4/2004	Bloebaum
6,725,159	B2	4/2004	Krasner
6,731,940	B1	5/2004	Nagendran
6,734,821	B2	5/2004	Van Diggelen
6,738,013	B2	5/2004	Orler
6,738,800	B1	5/2004	Aquilon
6,741,842	B2	5/2004	Goldberg
6,745,038	B2	6/2004	Callaway, Jr.
6,747,596	B2	6/2004	Orler
6,748,195	B1	6/2004	Phillips
6,751,464	B1	6/2004	Burg
6,756,938	B2	6/2004	Zhao
6,757,544	B2	6/2004	Rangarajan
6,772,340	B1	8/2004	Peinado
6,775,655	B1	8/2004	Peinado
6,775,802	B2	8/2004	Gaal
6,778,136	B2	8/2004	Gronemeyer
6,778,885	B2	8/2004	Agashe
6,781,963	B2	8/2004	Crockett
6,788,249	B1	9/2004	Farmer
6,795,699	B1	9/2004	McCraw
6,799,050	B1	9/2004	Krasner
6,801,124	B2	10/2004	Naitou
6,801,159	B2	10/2004	Swope
6,804,524	B1	10/2004	Vandermeijden
6,807,534	B1	10/2004	Erickson
6,810,323	B1	10/2004	Bullock
6,813,560	B2	11/2004	van Diggelen
6,816,111	B2	11/2004	Krasner
6,816,710	B2	11/2004	Krasner
6,816,719	B1	11/2004	Heinonen
6,816,734	B2	11/2004	Wong
6,820,269	B2	11/2004	Baucke et al.
6,829,475	B1	12/2004	Lee
6,832,373	B2	12/2004	O'Neill
6,833,785	B2	12/2004	Brown
6,839,020	B2	1/2005	Geier
6,839,021	B2	1/2005	Sheynblat
6,842,715	B1	1/2005	Gaal
6,853,849	B1	2/2005	Tognazzini
6,853,916	B2	2/2005	Fuchs
6,856,282	B2	2/2005	Mauro
6,861,980	B1	3/2005	Rowitch
6,865,171	B1	3/2005	Nilsson
6,865,395	B2	3/2005	Riley
6,867,734	B2	3/2005	Voor
6,873,854	B2	3/2005	Crockett
6,885,940	B2	4/2005	Brodie
6,888,497	B2	5/2005	King
6,888,932	B2	5/2005	Snip
6,895,238	B2	5/2005	Newell
6,895,249	B2	5/2005	Gaal
6,895,324	B2	5/2005	Straub
6,900,758	B1	5/2005	Mann
6,903,684	B1	6/2005	Simic
6,904,029	B2	6/2005	Fors
6,907,224	B2	6/2005	Younis
6,907,238	B2	6/2005	Leung
6,912,395	B2	6/2005	Benes
6,915,208	B2	7/2005	Garin
6,917,331	B2	7/2005	Gronemeyer
6,930,634	B2	8/2005	Peng
6,937,187	B2	8/2005	Van Diggelen
6,937,872	B2	8/2005	Krasner
6,941,144	B2	9/2005	Stein
6,944,540	B2	9/2005	King
6,947,772	B2	9/2005	Minear
6,950,058	B1	9/2005	Davis
6,956,467	B1	10/2005	Mercado, Jr.
6,957,073	B2	10/2005	Bye
6,961,562	B2	11/2005	Ross
6,965,754	B2	11/2005	King
6,965,767	B2	11/2005	Maggenti
6,970,917	B1	11/2005	Kushwaha
6,973,166	B1	12/2005	Tsumpes
6,973,320	B2	12/2005	Brown
6,975,266	B2	12/2005	Abraham
6,978,453	B2	12/2005	Rao
6,980,816	B2	12/2005	Rohles
6,985,105	B1	1/2006	Pitt et al.
6,996,720	B1	2/2006	DeMello
6,998,985	B2	2/2006	Reisman
6,999,782	B2	2/2006	Shaughnessy
7,020,440	B2	3/2006	Watanabe
7,024,321	B1	4/2006	Deninger
7,024,393	B1	4/2006	Peinado
7,047,411	B1	5/2006	DeMello
7,064,656	B2	6/2006	Belcher et al.
7,065,351	B2	6/2006	Carter
7,065,507	B2	6/2006	Mohammed
7,071,814	B1	7/2006	Schorman
7,079,857	B2	7/2006	Maggenti
7,103,018	B1	9/2006	Hansen
7,103,574	B1	9/2006	Peinado
7,106,717	B2	9/2006	Rousseau
7,136,838	B1	11/2006	Peinado
7,151,946	B2	12/2006	Maggenti
7,177,623	B2	2/2007	Baldwin
7,203,752	B2	4/2007	Rice
7,209,969	B2	4/2007	Lahti
7,218,940	B2	5/2007	Niemenmaa
7,221,959	B2	5/2007	Lindquist
7,269,413	B2	9/2007	Kraft
7,301,494	B2	11/2007	Waters
7,324,823	B1	1/2008	Rosen
RE42,927	E	11/2011	Want
8,190,169	B2	5/2012	Shim
8,314,683	B2	11/2012	Pfeffer
8,442,807	B2	5/2013	Ramachandran
8,649,806	B2 *	2/2014	Cuff H04W 64/006 455/404.1
2001/0011247	A1	8/2001	O'Flaherty
2002/0037735	A1	3/2002	Maggenti
2002/0052214	A1	5/2002	Maggenti
2002/0061760	A1	5/2002	Maggenti
2002/0069529	A1	6/2002	Wieres
2002/0102999	A1	8/2002	Maggenti
2002/0112047	A1	8/2002	Kushwaha
2002/0135504	A1	9/2002	Singer
2002/0173317	A1	11/2002	Nykanen
2002/0198632	A1	12/2002	Breed
2003/0009602	A1	1/2003	Jacobs
2003/0037163	A1	2/2003	Kitada
2003/0065788	A1	4/2003	Salomaki

(56) **References Cited**

U.S. PATENT DOCUMENTS

2003/0078064 A1 4/2003 Chan
2003/0081557 A1 5/2003 Mettala
2003/0101329 A1 5/2003 Lahti
2003/0101341 A1 5/2003 Kettler
2003/0103484 A1 6/2003 Oommen
2003/0112941 A1 6/2003 Brown
2003/0114157 A1 6/2003 Spitz
2003/0119528 A1 6/2003 Pew
2003/0131023 A1 7/2003 Bassett
2003/0153340 A1 8/2003 Crockett
2003/0153341 A1 8/2003 Crockett
2003/0153342 A1 8/2003 Crockett
2003/0153343 A1 8/2003 Crockett
2003/0161298 A1 8/2003 Bergman
2003/0204640 A1 10/2003 Sahinoja et al.
2003/0223381 A1 12/2003 Schroderus
2004/0002326 A1 1/2004 Maher
2004/0044623 A1 3/2004 Wake
2004/0046667 A1 3/2004 Copley
2004/0064550 A1 4/2004 Sakata
2004/0068724 A1 4/2004 Gardner
2004/0090121 A1 5/2004 Simonds
2004/0204806 A1 10/2004 Chen
2004/0205151 A1 10/2004 Sprigg
2004/0229632 A1 11/2004 Flynn
2004/0257273 A1 12/2004 Benco
2005/0003797 A1 1/2005 Baldwin
2005/0028034 A1 2/2005 Gantman
2005/0039178 A1 2/2005 Marolia
2005/0041578 A1 2/2005 Huotari
2005/0086340 A1 4/2005 Kang
2005/0086467 A1 4/2005 Asokan
2005/0112030 A1 5/2005 Gauss
2005/0136895 A1 6/2005 Thenthiruperai
2005/0170856 A1 8/2005 Keyani
2005/0172217 A1 8/2005 Leung
2005/0174987 A1 8/2005 Raghav
2005/0209995 A1 9/2005 Aksu
2005/0233735 A1 10/2005 Karaoguz
2005/0246217 A1 11/2005 Horn
2005/0259675 A1 11/2005 Tuohino
2006/0053225 A1 3/2006 Poikselka
2006/0058045 A1 3/2006 Nilsen
2006/0073810 A1 4/2006 Pyhalammi
2006/0074618 A1 4/2006 Miller
2006/0090136 A1 4/2006 Miller
2006/0097866 A1 5/2006 Adamczyk
2006/0212558 A1 9/2006 Sahinoja
2006/0212562 A1 9/2006 Kushwaha
2006/0234639 A1 10/2006 Kushwaha
2006/0234698 A1 10/2006 Fok et al.
2006/0246920 A1 11/2006 Shim
2007/0026854 A1 2/2007 Nath
2007/0030116 A1 2/2007 Feher
2007/0030539 A1 2/2007 Nath
2007/0030973 A1 2/2007 Mikan
2007/0049287 A1 3/2007 Dunn
2007/0186105 A1 8/2007 Bailey
2007/0191025 A1 8/2007 McBrierty
2007/0271596 A1 11/2007 Boubion
2008/0026723 A1 1/2008 Han
2008/0160980 A1 7/2008 Harris
2008/0198989 A1 8/2008 Contractor
2008/0318591 A1 12/2008 Oliver
2009/0058830 A1 3/2009 Herz
2009/0140851 A1 6/2009 Graves
2009/0204815 A1 8/2009 Dennis
2009/0222388 A1 9/2009 Hua
2009/0271486 A1 10/2009 Ligh
2009/0311992 A1 12/2009 Jagetiya
2009/0328135 A1 12/2009 Szabo
2010/0024045 A1 1/2010 Sastry
2010/0050251 A1 2/2010 Speyer
2010/0197318 A1 8/2010 Petersen
2010/0205542 A1 8/2010 Walman
2010/0285763 A1 11/2010 Ingrassia
2010/0285814 A1 11/2010 Price
2010/0308993 A1 12/2010 Ma

OTHER PUBLICATIONS

Internal Search Report received in PCT/US2009/05575 dated Dec. 3, 2009.
International Search Report received in PCT/US2011/01198 dated Aug. 6, 2012.
Internal Search Report received in PCT/US2011/000671 dated Jul. 27, 2011.
Internal Search Report received in PCT/US2011/000671 dated Apr. 25, 2012.
International Search Report in PCT/US2010/001134 dated Oct. 31, 2011.
Internal Search Report received in PCT/US2011/00950 dated Sep. 16, 2011.
International Search Report in PCT/US2011/00950 dated Apr. 30, 2012.
International Search Report received in PCT/US2012/000374 dated Nov. 20, 2012.
International Report on Patentability received in PCT/US2012/000374 dated Sep. 5, 2013.

* cited by examiner

FIG. 1


316
INTERNET
LOCATION BASED SERVICES (LBS)
318
400
AGGREGATE LOCATION DYNOMETER (ALD)
302
304
306
NETWORK MONITOR
CROWD RISK DETERMINANT
ALERT MODULE
322
320
WIRELESS CARRIER NETWORK
PUBLIC SAFETY PERSONNEL
324
ACCEPTABLE / NON-ACCEPTABLE CROWD SHAPE DB
CONFIGURABLE PARAMETER THRESHOLD DB
HISTORICAL WIRELESS DEVICE LOCATION TRENDS AND STATISTICS DB
RISK RULES DB
308
310
312
314

FIG. 2


NETWORK MONITOR 302
MONITOR TRAFFIC
500
COMPARE TRAFFIC PARAMETERS WITH CONFIGURABLE PARAMETER THRESHOLD DB
510
302
520
VIRAL EVENT OCCURING?
YES
TO CROWD RISK DETERMINANT 304
NO
LOG LOCATION DATA IN HISTORICAL WIRELESS DEVICE LOCATION TRENDS AND STATISTICS DB
530

FIG. 3


CROWD RISK DETERMINANT 304
FROM NETWORK MONITOR 302
INITIATE LOCATION PUSH/PULL
540
COMPARE VIRAL PATTERN WITH PARAMETERS STORED IN RISK RULES DB
550
304
560
PUBLIC SAFETY RISK?
YES
TO ALERT MODULE 306
NO
LOG LOCATION DATA IN HISTORICAL WIRELESS DEVICE LOCATION TRENDS AND STATISTICS DB
530

FIG. 4


ALERT MODULE 306
FROM CROWD RISK DETERMINANT 304
PUBLIC SAFETY RISK LOGISTICS
700
710
ALERT AUTHORITIES
320
PUBLIC SAFETY PERSONNEL
306
IS PUBLIC SAFETY EVENT PROGRAMMED TO REQUIRE ADDITIONAL LOCATION INFORMATION?
720
YES
540
INITIATE LOCATION PUSH / PULL
NO
530
730
END
LOG LOCATION DATA IN HISTORICAL WIRELESS DEVICE LOCATION TRENDS AND STATISTICS DB



FIG. 5



FIG. 6



FIG. 7

AGGREGATE LOCATION DYNOMETER (ALD)

The present application is a continuation of U.S. application Ser. No. 14/176,691, entitled "Aggregate Location Dynometer (ALD)", filed on Feb. 10, 2014; which is a continuation of U.S. application Ser. No. 13/317,996 entitled "Aggregate Location Dynometer (ALD)", filed on Nov. 2, 2011, now U.S. Pat. No. 8,649,806; which claims priority from U.S. Provisional Application No. 61/573,112, entitled "Aggregate Location Dynometer (ALD)", filed Sep. 2, 2011, the entirety of all three of which are expressly incorporated herein by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention relates generally to wireless telecommunications. More particularly, it relates to cell location services, cell network trafficking and analysis of location information.

2. Background of Related Art

Location based applications obtain a geographic position of a particular wireless device and provide services accordingly. Location based services (LBS) prevail in today's market due to an incorporation of tracking technology in handheld devices.

Location based pull services allow a wireless device user to locate another wireless device. Current location services are generally focused on individual wireless device user applications.

SUMMARY OF THE INVENTION

In accordance with the principles of the present invention, a method of alerting to a problematic crowd risk in a given geographical location, comprises an Aggregate Location Dynometer (ALD). The Aggregate Location Dynometer (ALD) utilizes location based services (LBS) to analyze aggregate location information pertaining to a multitude of wireless devices, to detect potential crowd risks.

An Aggregate Location Dynometer (ALD) resides in a physical network server, in accordance with the present invention, and comprises three main components: a Network Monitor, a Crowd Risk Determinant, and an Alert Module.

The Network Monitor monitors a wireless network for indication of a possible impending viral event, in accordance with the principles of the present invention. In particular, the Network Monitor utilizes location based services (LBS) to monitor the formation of a plurality of wireless devices at a given point in a wireless network, e.g., a given base station (BS). The Network Monitor compares obtained traffic parameters pertaining to monitored wireless traffic, with historical traffic parameters having to do with crowd risk determination, to determine if a viral event may be occurring or impending. A snapshot look at current location data collected by the Network Monitor is subsequently logged in an appropriate historical database.

In accordance with the principles of the present invention, the Crowd Risk Determinant analyzes location information to determine if a viral event triggered by the Network Monitor, also indicates a crowd safety risk. In particular, the Crowd Risk Determinant initiates a location request to obtain location information pertaining to a multitude of wireless devices in a given area, regarding a viral event that has been triggered by the Network Monitor. The Crowd Risk Determinant compares the viral pattern formed by the shape and movement of wireless devices in locations observed, with predetermined risk rules to determine if the viral event is also a crowd safety risk. The observed viral pattern is subsequently logged in an appropriate historical database.

The Alert Module, in accordance with the principles of the present invention, alerts proper authorities in an event of a crowd safety risk. The Crowd Risk Determinant triggers the Alert Module to alert of an impending crowd problem when crowd risk has exceeded a given threshold.

The Aggregate Location Dynometer (ALD) utilizes historical databases, in accordance with the present invention, to maintain location-based information indicating possible viral events associated with a plurality of wireless devices. Historical databases include an Acceptable/Non-Acceptable Crowd Shape database, a Configurable Parameter Threshold database, a Historical Wireless Device Location Trends database, and a Risk Rules database.

BRIEF DESCRIPTION OF THE DRAWINGS

Features and advantages of the present invention will become apparent to those skilled in the art from the following description with reference to the drawings, in which:

FIG. **1** depicts an exemplary Aggregate Location Dynometer (ALD), in accordance with the principles of the present invention.

FIG. **2** depicts the flow of an exemplary Network Monitor of the Aggregate Location Dynometer (ALD), in accordance with the principles of the present invention.

FIG. **3** depicts the flow of an exemplary Crowd Risk Determinant of the Aggregate Location Dynometer (ALD), in accordance with the principles of the present invention.

FIG. **4** depicts the flow of an exemplary Alert Module of the Aggregate Location Dynometer (ALD), in accordance with the principles of the present invention.

FIG. **5** denotes first exemplary Aggregate Location Dynometer (ALD) location results, in accordance with the principles of the present invention.

FIG. **6** denotes second exemplary Aggregate Location Dynometer (ALD) location results, in accordance with the principles of the present invention.

FIG. **7** denotes third exemplary Aggregate Location Dynometer (ALD) location results, in accordance with the principles of the present invention.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

Thus far, location capabilities have been concerned with locating an individual wireless device. Yet, there is such a vast abundance of individuals populating the nation's major cities. The present inventor has appreciated the benefits of using location based services (LBS) to obtain sets of aggregate location data corresponding to a number and pattern of wireless devices within an area, region, city, etc. of interest.

The present invention introduces an Aggregate Location Dynometer (ALD), an analytical server utilizing location based services (LBS) on a network to predict public safety risks, e.g., the unexpected impending formation of a flash mob, or a riot, etc.

The Aggregate Location Dynometer (ALD) analyzes a bird's-eye view of people formation, presuming those individuals possess respective handheld wireless devices that permit collection of current location information, whether that current location information be obtained from the wireless devices themselves, and/or from a network-based location server.

In accordance with the principles of the present invention, the Aggregate Location Dynometer (ALD) predicts public safety risk in a given geographical area through evaluation of the positioning and movement of wireless devices. The Aggregate Location Dynometer (ALD) monitors wireless device network traffic to predict an impending viral event. If a possible impending viral event is sensed from a general monitoring of wireless traffic, the Aggregate Location Dynometer (ALD) may request impending viral location information pertaining to clusters of wireless devices in a vicinity of the possible event, to more accurately assess crowd risk.

Crowd risk is assessed based upon given wireless network traffic parameters such as the number of wireless devices in communication with a given base station (e.g., a density), the shape formed by representations of the individual locations of the densest areas where active wireless devices are currently located, and/or the movement of the wireless devices within the region as defined.

Markers, each representing a wireless device at a given location at a given time, may be displayed on a display of the Aggregate Location Dynometer (ALD). The markers may represent wireless devices served within the given region, whether actively communicating with another wireless device, or merely sensed as present.

The present invention preferably provides an alert of a possible impending crowd related public safety risk in real time, as the crowd risk arises, informing emergency personnel as early as possible, even before such event is consummated.

FIG. **1** depicts an exemplary Aggregate Location Dynometer (ALD) **400**, in accordance with the principles of the present invention.

In particular, an Aggregate Location Dynometer (ALD) **400** determines crowd safety risk with the help of location based services (LBS) **318**, as depicted in FIG. **1**.

The Aggregate Location Dynometer (ALD) **400** is generally based in a server in a wireless network **322**. Three main components form the Aggregate Location Dynometer (ALD) **400**: a Network Monitor **302**, a Crowd Risk Determinant **304**, and an Alert Module **306**.

The Network Monitor **302** begins the risk determination process of the Aggregate Location Dynometer (ALD) **400** by monitoring the network for indication of a possible viral event, in accordance with the principles of the present invention. Determination of a viral event is the first step in the escalation-based response of the Aggregate Location Dynometer (ALD) **400**.

The Crowd Risk Determinant **304** assesses location information pertaining to a possible viral event triggered by the Network Monitor **302**. The Crowd Risk Determinant **304** determines if a viral event also indicates a public safety risk.

The Alert Module **306** performs predetermined responsive measures to alert appropriate public safety personnel **320** in the event of a possible or probable or current public safety risk.

Historical databases are empirically determined and maintained in the Aggregate Location Dynometer (ALD) **400** for use in crowd risk assessment. The historical databases preferably store sets of aggregate current location information pertaining to trackable wireless devices. Exemplary historical databases accessible by the Aggregate Location Dynometer (ALD) **400** include but are not limited to a Historical Wireless Device Location Trends and Statistics database **312**, a Configurable Parameter Threshold database **310**, a Risk Rules database **314**, and an Acceptable/Non-Acceptable Crowd Shape database **308**.

The Historical Wireless Device Location Trends and Statistics database **312**, as shown in FIG. **1**, preferably stores sets of instantaneous aggregate location information obtained over a period of time. Data stored in the Historical Wireless Device Location Trends and Statistics database **312** provides empirical evaluation of crowd activities used to detect a crowd trend. The Aggregate Location Dynometer (ALD) **400** preferably uses data stored in the Historical Wireless Device Location Trends and Statistics database **312** to determine if a current situation is considered to be 'normal' to the monitored area, or abnormal, triggering a viral event. The data maintained in the Historical Wireless Device Location Trends and Statistics database **312** is preferably refreshed over time.

The Configurable Parameter Threshold database **310**, as depicted in FIG. **1**, preferably comprises a set of configurable location-based parameters and thresholds including density, clustering, spread, geographical boundary, motion trends, and/or special events occurring in particular areas. The Configurable Parameter Threshold database **310** can also include non-location based parameters such as time of day and/or message content. The parameters stored in the Configurable Parameter Threshold database **310** are accessed by the Network Monitor **302** to assist in detecting a viral event.

The Risk Rules database **314**, as shown in FIG. **1**, preferably comprises a set of configurable location-based parameters and thresholds including density, clustering, spread, geographical boundary, motion trends, and/or special events occurring in particular areas. The Risk Rules database **314** can also include non-location based parameters such as time of day and/or message content. The parameters stored in the Risk Rules database **314** are accessed by the Crowd Risk Determinant **304** to assist in determining if a viral event also indicates a public safety risk.

The Acceptable/Non-Acceptable Crowd Shape database **308**, as shown in FIG. **1**, holds empirically determined past, historical cluster information regarding acceptable and/or non-acceptable past shape formations of clustered wireless devices. Specific shape parameters stored in the Acceptable/Non-Acceptable Crowd Shape database **308** are accessed by the Crowd Risk Determinant **304** to assist in determining if a viral event also indicates a public safety risk.

A viral event is the first state of alarm in the multi-state risk determination process of the Aggregate Location Dynometer (ALD) **400**. A viral event is defined as occurring when one or more predefined parameter thresholds have been surpassed, as determined in the exemplary embodiment in the Network Monitor **302**. The occurrence of a viral event does not necessarily infer a definite public safety risk. Instead, a viral event triggers the Crowd Risk Determinant **304** to further analyze a potentially malignant event more closely. For example, the Crowd Risk Determinant **304** provides a closer inspection of aggregate current location information, e.g., via use of a location-based push/pull service. A match of more detailed location information to a historical pattern leading to crowd risk may determine that a particular viral event also indicates a likely public safety risk.

A public safety risk confirms a compromise in crowd safety, e.g., the impending formation of a flash mob, or a riot, etc. Determination of a public safety risk triggers the Alert Module **306** to implement proper public safety response services.

The Network Monitor **302** begins the risk determination process of the Aggregate Location Dynometer (ALD) **400**, by monitoring the network for indication of a possible viral event, in accordance with the principles of the present invention.

Moreover, the Network Monitor **302** retrieves subsequent sets of instantaneous aggregate location information. Location information triggered by the Network Monitor **302** may be portrayed in the form of snapshots displayed on a display of the Aggregate Location Dynometer (ALD) **400**. Snapshots by the Network Monitor **302** comprise markers, each representing the location of individual wireless devices within a given region being monitored.

The Network Monitor **302** preferably obtains information regarding the number of wireless devices in a geographical area, at a given time, supported by a particular wireless network carrier (e.g., the number of wireless devices sending messages over a wireless network via a particular base station (BS) **324**). The Network Monitor **302** uses predefined parameters and thresholds to determine if the monitored network indicates that a viral event may be occurring or impending (e.g., surpassed parameter thresholds possibly indicative of an excessive number and/or use of wireless devices for a given area, cell tower, etc.).

For instance, a Maximum Number of Devices parameter may indicate the maximum number of wireless devices that may be present within range of a particular base station (BS) **324** at a given time before a possible viral event is triggered. The Maximum Number of Devices parameter may be set manually, or empirically determined (e.g., the average number of devices present at a particular base station (BS) **324** over a course of time, as determined by historical data stored in the Historical Wireless Device Location Trends and Statistics database **312**).

The Network Monitor **302** triggers a possible viral event if a predefined parameter threshold has been surpassed (e.g., a given density of current location markers each representing a separate wireless device, or a directed convergence of at least two highly dense clusters of markers toward each other at a significant rate of speed is or has occurred, etc.).

The Network Monitor **302** preferably tallies the number of wireless devices in each instantaneous aggregate location snapshot that is captured. Predetermined parameters and thresholds are used to assess the number (e.g., the density) of wireless devices in a particular area to determine whether or not a possible viral event is occurring.

The Maximum Number of Devices parameter may alternatively be set to indicate the maximum number of wireless devices that may be present in an instantaneous aggregate location snapshot before a possible viral event is triggered. If the number of devices present in a given snapshot exceeds the Maximum Value of Devices parameter established for the respective location, a viral event may be triggered.

The Network Monitor **302** also preferably tallies the difference in the number of wireless devices in a given area, from one consecutive instantaneous aggregate location snapshot to the next. If the difference in the number of wireless devices from snapshot to snapshot exceeds a predefined value in a number of consecutive snapshots for a given area, base station, etc., then a viral event may be triggered. Thresholds for such a predefined Maximum Difference in Number of Wireless Devices parameter and a predefined Interval of Consecutive Snapshots parameter may be set manually, or empirically determined (e.g., the average difference in number of devices in consecutive instantaneous aggregate location snapshots capturing a particular area, e.g., a number of square feet, a particular base station (BS), etc., over a course of time, supported by a particular network carrier, as recorded in the Historical Wireless Device Location Trends and Statistics database **312**).

FIG. **2** depicts the flow of an exemplary Network Monitor **302** of the Aggregate Location Dynometer (ALD) **400**, in accordance with the principles of the present invention.

In particular, as shown in step **500** of FIG. **2**, the Network Monitor **302** preferably continuously, or at least periodically or intermittently, monitors network traffic.

In step **510**, monitored wireless data traffic is inspected for the presence of abnormal events, e.g., excessive volume for the time of day, etc. Configurable thresholds for the monitored parameters may be dynamic over the course of the day and even for traffic for any given tower or base station. The configurable thresholds for monitored parameters may be stored in the Configurable Parameter Threshold database **310**.

As shown in step **520**, if one or more parameter thresholds are exceeded, a viral event may be triggered. In response, the Network Monitor **302** triggers the Crowd Risk Determinant **304** to perform a location-based push/pull service to determine the location of each trackable wireless device within a particular geographic area (e.g., communicating through given base stations or antennas).

When parameter thresholds are not surpassed, indicating that a viral event is not occurring, location data may be logged in the Historical Wireless Device Location Trends and Statistics database **312**, as depicted in step **530**. Location data logged in the Historical Wireless Device Location Trends and Statistics database **312** may be used by the Crowd Risk Determinant **304** for future analyses of crowd risk.

FIG. **3** depicts the flow of an exemplary Crowd Risk Determinant **304** of the Aggregate Location Dynometer (ALD) **400**, in accordance with the principles of the present invention.

In particular, the Crowd Risk Determinant **304** performs a location-based push/pull service to obtain location information pertaining to trackable wireless devices in a given area regarding a respective viral event triggered by the Network Monitor **302**, as shown in step **540** of FIG. **3**.

In step **550**, collected location data is analyzed to assess the viral event that is occurring. The Crowd Risk Determinant **304** uses bounds and priorities set forth in the Risk Rules database **314** to determine if a possible viral event indicates a public safety risk. A viral pattern may or may not imply public safety risk. In step **560**, if a public safety risk is determined, the Crowd Risk Determinant **304** triggers the Alert Module **306** to take responsive public safety measures. Location data associated with a public safety risk is logged **530** in the Historical Wireless Device Location Trends and Statistics database **312**.

If the Crowd Risk Determinant **304** confirms that a particular viral event does not indicate a public safety risk, the Aggregate Location Dynometer (ALD) **400** is triggered to routinely log location data **530** in the Historical Wireless Device Location Trends and Statistics database **312** for potential future analyses.

Determination of a public safety risk in the Crowd Risk Determinant **304** triggers the Alert Module **306** to implement proper public safety response services. An Alert Module **306** is the final step in the risk determination process of the Aggregate Location Dynometer (ALD) **400**.

FIG. **4** depicts the flow of an exemplary Alert Module **306** of the Aggregate Location Dynometer (ALD) **400**, in accordance with the principles of the present invention.

In particular, as shown in step **700** of FIG. **4**, the Alert Module **306** is triggered by the Crowd Risk Determinant **304** and supplied the predetermined conditions constituting how to handle a determined public safety risk.

The Alert Module **306** immediately alerts the proper authorities **320** in the presence of a public safety risk, as depicted in step **710**.

Subsequent aggregate data collections may be made by the Alert Module **306** in step **720**. A particular public safety event may be programmed to result in multiple aggregate location data collections, set to occur at specific intervals. Moreover, a particular risk determination result may be configured to act as a triggered push/pull service **540** to acquire additional location data. Subsequent location information is routinely logged in the Historical Wireless Devices Location Trends and Statistics database **530**.

Configurable parameters are maintained in the Risk Rules database **314** to assist the Crowd Risk Determinant **304** in determining if location information pertaining to a viral event indicates a likely public safety risk. Factors for risk determination include but are not limited to the shape a cluster of location markers representing individual wireless devices of given density is forming, whether or not markers are spreading out or coming together, and/or at what rate of change a cluster of wireless devices is moving. Factors for risk determination also include the behavior of collective XY location coordinates of the most dense clusters of wireless devices, to where the most dense clusters of wireless devices of concern are moving, and/or whether or not a cluster of wireless devices in a particular location makes sense given the time of day.

For instance, empirical data may indicate that it is unusual for there to be a large number of wireless devices present downtown after business hours, or after a time when local bars and clubs have closed for the night. In this case, a configurable threshold may be set for a combination of location and time of day parameters (e.g., to articulate the number of wireless devices that must be present within a defined downtown region, after a given hour) to trigger a public safety risk. A configurable parameter threshold (e.g., specifying the number of wireless devices capable of inhabiting a particular geographic expanse or particular shape of device formation, or a given density within that region) may manually or empirically be set. If a parameter threshold is surpassed, the Crowd Risk Determinant **304** informs the Alert Module **306** of the development of a public safety risk.

The shape of a cluster of wireless devices may often offer significant clues to crowd risk potential. When location information is collected, the best-fit shape of dense clusters formed by accumulation of wireless devices in a given area may be determined. The best-fit shape of a cluster of wireless devices may be compared against data contained in the historical Acceptable/Non-Acceptable Crowd Shape database **308** to determine danger potential. Different thresholds may be set for like parameters based on varying location.

FIG. **5** denotes first exemplary Aggregate Location Dynometer (ALD) **400** location results, in accordance with the principles of the present invention.

In particular, the large oval shape **101** formed by markers representing individual wireless devices in the given geographical area **200** shown in FIG. **5**, may be interpreted as a group of individuals enjoying a sporting event in a stadium. Factors to consider are time of day and scheduled events. The example in FIG. **5** uses precise location.

FIG. **6** denotes second exemplary Aggregate Location Dynometer (ALD) **400** location results, in accordance with the principles of the present invention.

In particular, the pattern **102** in the geographical area **200** shown in FIG. **6** may be interpreted as cell sites pertaining to trackable individuals, assuming most individuals carry wireless devices. The same pattern may mean different things at different hours of the day. The exemplary location result shown in FIG. **6** uses coarse location.

FIG. **7** denotes third exemplary Aggregate Location Dynometer (ALD) **400** location results, in accordance with the principles of the present invention.

In particular, the crescent shape **103** in the geographical area **200** shown in FIG. **7** is recognized as a pattern to be wary of. This crescent shape may represent a variety of different occurrences (e.g., a protest in front of a given location such as a court house, a famous author at a bookstore, etc.). The exemplary location result shown in FIG. **7** uses precise location.

A rate-based parameter threshold may also or alternatively be set to define an acceptable rate at which wireless devices would otherwise normally inhabit a geographic area. For instance, if over a certain number of wireless devices enter an area in under a given amount of time (e.g., if three hundred wireless devices rush into a central pre-defined location in under ten minutes) then a public safety risk may be triggered.

Message content may be analyzed as an attribute for risk determination in response to a viral traffic event. For instance, a determination of the most frequent phrases may be matched against a database of suspected terms (e.g., "meet at the Lincoln Memorial", etc.).

Motion trends are also analyzed to assess crowd risk. The Crowd Risk Determinant **304** preferably determines whether the accumulation of wireless devices is becoming more or less dense about a central location and whether or not this behavior is expected based on trends and configured thresholds established for particular locations.

Precise accuracy of each individual device location is not extremely important in the present invention. Instead, focus lies in the volume, density, shape and movement of data points collected. Serving cell tower locations for each wireless device may be sufficient to satisfy initial triggering requirements for a possible viral event. The Aggregate Location Dynometer (ALD) **400** is concerned with aggregate location data as opposed to data involving individual device locations. Data regarding parameters such as special events, geographical boundaries, motion trends, density, clustering, spread, time of day and/or message content relating to trackable wireless devices are recorded in the Historical Wireless Device Location Trends and Statistics database **312**, as opposed to exact locations of specific wireless devices. Anonymity regarding precise locations of specific wireless devices alleviates some concern surrounding the privacy of individuals during location based services (LBS), as used within the present invention.

An Aggregate Location Dynometer (ALD) **400** has benefit to entities other than emergency management and crowd risk assessment parties. For instance, the present invention may also be used to estimate location trends in cities, to rank areas such as parks and beaches by volume of visitors, and even to peg traffic patterns. Historical crowd data need not represent a public safety issue, e.g., it may merely relate to city planning or disaster recovery. Thus, data collected while scanning for crowd risk provides cities, states and government with valuable information.

Though, preferably all wireless devices in a given area would be monitored for crowd gathering tendencies, it is also within the principles of the present invention to monitor only those devices by the relevant wireless carrier providing Location Dynometer (ALD) **400** services.

The present invention greatly benefits police, fire and general emergency response personnel **320** desiring early warning about possible crowd related risks, e.g., riots. Moreover,

the present invention is intended to combat nefarious cell technology to spawn mobs and riots without resorting to network restrictions.

While the invention makes use of the current location data of preferably all wireless devices within a given region, area, etc., the invention also preferably makes distinction between the current mode of operation of the wireless devices being analyzed for a possible public safety risk. For instance, analysis of the density, shape, movement, etc. in determining a possible public safety risk may analyze only wireless devices in active mode.

While the invention has been described with reference to the exemplary embodiments thereof, those skilled in the art will be able to make various modifications to the described embodiments of the invention without departing from the true spirit and scope of the invention.

What is claimed is:

1. An aggregate location dynometer in a physical wireless network server, said aggregate location dynometer comprising:

a network monitor to monitor a wireless network for an indication of a potential viral event indicated by an aggregation of current locations of a plurality of physical wireless devices associated with said potential viral event; and

a crowd risk determinant to assess said aggregation of said current locations of said plurality of physical wireless devices pertaining to said potential viral event triggered by said network monitor.

2. The aggregate location dynometer in a physical wireless network server, said aggregate location dynometer according to claim **1**, further comprising:

an alert module to initiate an alert message relating to a public safety risk determined from said potential viral event.

3. The aggregate location dynometer in a physical wireless network server, said aggregate location dynometer according to claim **1**, further comprising:

an historical database maintaining a geographic region associated with said potential viral event.

4. The aggregate location dynometer in a physical wireless network server, said aggregate location dynometer according to claim **1**, further comprising:

an historical database maintaining a plurality of acceptable crowd shapes, a crowd shape being defined by a past aggregation of said current locations of said plurality of physical wireless devices associated with a known acceptable viral event.

5. The aggregate location dynometer in a physical wireless network server, said aggregate location dynometer according to claim **1**, further comprising:

an historical database maintaining a plurality of unacceptable crowd shapes, a crowd shape being defined by a past aggregation of said current locations of said plurality of physical wireless devices associated with a known unacceptable viral event.

6. The aggregate location dynometer in a physical wireless network server, said aggregate location dynometer according to claim **1**, further comprising:

a configurable parameter defining a threshold of a crowd shape becoming unacceptable and thus initiating said crowd risk.

7. The aggregate location dynometer in a physical wireless network server, said aggregate location dynometer according to claim **1**, further comprising:

an historical database maintaining a plurality of crowd shape trends based on historical locations of physical wireless devices during previous known viral events.

8. A method of alerting to a problematic crowd risk based on location based services (LBS), comprising:

monitoring wireless traffic for a potential impending viral event associated with a formation by an aggregation of current locations of a plurality of physical wireless devices within a given region;

requesting location information associated with said plurality of physical wireless devices; and

determining a crowd risk of said aggregation of said current locations of said plurality of physical wireless devices based on a crowd shape of said aggregation of said current locations of said plurality of physical wireless devices.

9. The method of alerting to a problematic crowd risk based on location based services (LBS) according to claim **8**, further comprising:

triggering a crowd alert message when said determined crowd risk is above a given threshold.

10. The method of alerting to a problematic crowd risk with location based services (LBS) according to claim **8**, wherein:

said crowd risk of said aggregation of said plurality of physical wireless devices is further determined based on a movement of said aggregation of said plurality of physical wireless devices.

11. The method of alerting to a problematic crowd risk with location based services (LBS) according to claim **10**, wherein said monitoring wireless traffic comprises:

monitoring wireless traffic at a given point in a wireless network; and

comparing a given traffic parameter associated with said aggregation of said current locations of said plurality of physical wireless devices, with an historical traffic parameter associated with a previous problematic crowd formation.

12. The method of alerting to a problematic crowd risk with location based services (LBS) according to claim **11**, wherein:

said given point is at a given base station in said wireless network.

13. The method of alerting to a problematic crowd risk with location based services (LBS) according to claim **10**, further comprising:

logging a snapshot formation created by said aggregation of said current locations of said plurality of physical wireless devices.

14. The method of alerting to a problematic crowd risk with location based services (LBS) according to claim **10**, further comprising:

initiating a location request for each of said plurality of physical wireless devices.

15. The method of alerting to a problematic crowd risk with location based services (LBS) according to claim **9**, further comprising:

comparing a viral pattern formed by said aggregation of said current locations of said plurality of wireless devices to predetermined risk rules.

16. The method of alerting to a problematic crowd risk with location based services (LBS) according to claim **15**, further comprising:

logging said viral pattern.

* * * * *

Exhibit C

to

Complaint for Patent Infringement

Claim Chart[1] for the '054 Patent

[1] Plaintiff provides this exemplary claim chart for the purposes of showing one basis of infringement of one of the Patents-in-suit by Defendant's Accused Products as defined in the Complaint. This exemplary claim chart addresses the Accused Products broadly based on the fact that the Accused Products infringe in the same general way. Plaintiff reserves its right to amend and fully provide its infringement arguments and evidence thereof until its Preliminary and Final Infringement Contentions are later produced according to the court's scheduling order in this case.

CLAIM CHART

U.S. PATENT NO. 9,198,054 B2 – CLAIM 1

Claim 1	Corresponding Structure in Accused Systems – Apple Inc.
[1a] An aggregate location dynometer in a physical wireless network server, said aggregate location dynometer comprising:	Apple Inc. ("Apple") provides a contract tracing system that utilizes Bluetooth wireless technology to determine proximity of COVID-19 positive individuals and assess the risk of infection to alert users of this risk, known as the Exposure Notifications System. *See* https://www.google.com/covid19/exposurenotifications/ and https://covid19.apple.com/contacttracing. The Exposure Notifications System together with various equipment, services, components, and/or software utilized in providing the Exposure Notifications System collectively include an aggregate location dynometer (ALD) as described by the meaning of this claim. The Exposure Notifications System is made available by a system owned and/or operated by Apple. "Because infringement liability is not dependent on ownership, e.g., use of a system can infringe (35 U.S.C. § 271), infringement is not dependent on ownership of all limitations of a claim."
[1b] a network monitor to monitor a wireless network for an indication of a viral event;	Apple's Exposure Notifications System has the capability to monitor a wireless network through Bluetooth beacon keys to verify and store COVID-19 positive case information, and once validated, send indication of the positive cases to users through a wireless network. The users' devices then search the keys for matches indicating proximity to COVID-19 positive individuals. The following exemplifies this limitation's existence in Accused Systems:



Source:
(https://developer.apple.com/documentation/exposurenotification/supporting_exposure_notifications_express)

Alice and Bob don't know each other, but have a lengthy conversation sitting a few feet apart



Bob is positively diagnosed for COVID-19 and enters the test result in an app from his public health authority

Their phones exchange beacons with random Bluetooth identifiers (which change frequently)

A few days later...

With Bob's consent, his phone uploads the last 14 days of keys for his Bluetooth beacons to the server

Google

Alice continues her day unaware she had been near a potentially contagious person

Alice sees a notification on her phone



Alice's phone periodically downloads the Bluetooth beacon keys of everyone who has tested positive for COVID-19 in her region. A match is found with Bob's random Bluetooth identifiers.



Sometime later...

Alice's phone receives a notification with information about what to do next.

Google

	Source: (https://covid19-static.cdn-apple.com/applications/covid19/current/static/contact-tracing/pdf/ExposureNotification-FAQv1.2.pdf)
[1c] a location aggregator to obtain a location of each of a plurality of wireless devices associated with said viral event;	Apple's Exposure Notifications System includes the ability to exchange Bluetooth proximity identifiers between devices as a form of location aggregation relative to a device. Applications using the Exposure Notification framework "must specify the region for which they work." *See* https://developer.apple.com/documentation/bundleresources/information_property_list/endeveloperregion. The Exposure Notification framework also contains a method to determine if the user traveled outside of their app-associated region. *See* https://developer.apple.com/documentation/exposurenotification/enmanager/3644439-getusertraveled. This demonstrates that the Exposure Notifications System can access location data of each of a plurality of wireless devices associated with the viral event, which in this implementation can be exposure to a COVID-19 positive case. The following exemplifies this limitation's existence in Accused Systems:



Source: (https://covid19-static.cdn-apple.com/applications/covid19/current/static/contact-tracing/pdf/ExposureNotification-BluetoothSpecificationv1.2.pdf?1)

Alice and Bob don't know each other, but have a lengthy conversation sitting a few feet apart



Bob is positively diagnosed for COVID-19 and enters the test result in an app from his public health authority

Their phones exchange beacons with random Bluetooth identifiers (which change frequently)

A few days later...

With Bob's consent, his phone uploads the last 14 days of keys for his Bluetooth beacons to the server

Apps can only get more information via user consent

Google

Alice continues her day unaware she had been near a potentially contagious person

Alice sees a notification on her phone

Alice's phone periodically downloads the Bluetooth beacon keys of everyone who has tested positive for COVID-19 in her region. A match is found with Bob's random Bluetooth identifiers.

Sometime later...

Alice's phone receives a notification with information about what to do next.

	Source: (https://covid19-static.cdn-apple.com/applications/covid19/current/static/contact-tracing/pdf/ExposureNotification-FAQv1.2.pdf)
[1d] a crowd risk determinant, triggered by said network monitor, to determine a crowd risk based on an aggregation of said location of each of said plurality of wireless devices associated with said viral event; and	Apple's Exposure Notifications System includes an algorithm for determining risk after finding a match from the key data. The Exposure Notifications System can use the algorithm to determine exposure risk value based on risk parameters including but not limited to exposure proximity and duration. *See* https://developer.apple.com/documentation/exposurenotification/enexposureconfiguration; https://developer.apple.com/documentation/exposurenotification/enexposureconfiguration/exposure_risk_value_calculation_in_exposurenotification_version_1; and https://developer.apple.com/documentation/exposurenotification/exposure_parameter_limits. The following exemplifies this limitation's existence in Accused Systems:

13. How does the system know when I have been exposed?

The public health authority sets parameters to determine if someone has been exposed. For example, by defining the risk parameters based on estimated time the user has been in contact

Exposure Notifications - Frequently Asked Questions

with someone who has been diagnosed as positive for COVID-19 and the approximate distance between the users. Public health authorities will set a minimum threshold for time spent together.

To approximate distance, the system compares the Bluetooth signal strength between the two devices in contact. The closer the devices are, the higher the signal strength recorded. This signal strength can vary significantly based on factors like how the device is being held and as such this only provides an estimate of distance.

Source: (https://covid19-static.cdn-apple.com/applications/covid19/current/static/contact-tracing/pdf/ExposureNotification-FAQv1.2.pdf)



Source: (https://covid19-static.cdn-apple.com/applications/covid19/current/static/contact-tracing/pdf/ExposureNotification-BluetoothSpecificationv1.2.pdf?1)

[1e] an alert module to initiate an alert message relating to a public safety risk determined from an analysis of said viral event.	Apple's Exposure Notifications System contains functionality for sending alert messages to those with potential exposure to COVID-19 positive individuals as determined by the risk algorithm. It allows public health authorities to provide information to exposed individuals. The following exemplifies this limitation's existence in Accused Systems: **3. How can technology augment conventional contact tracing?** Technology can play an important role in those efforts. Mobile devices can be used in an automated and scalable way to help determine who has been exposed to a person who later reports a positive diagnosis of COVID-19. For example, they can be used to send a rapid notification to the exposed person with instructions on next steps. These notifications may be beneficial by alerting an exposed individual faster than they would be notified via conventional contact tracing. They will enable public health authorities to contact and provide guidance to the individual and, where appropriate, include them in conventional contact tracing efforts. Using digital exposure notifications is new and individual health authorities are determining how they best fit into their own public health systems. **Source:** (https://covid19-static.cdn-apple.com/applications/covid19/current/static/contact-tracing/pdf/ExposureNotification-FAQv1.2.pdf)

Alice and Bob don't know each other, but have a lengthy conversation sitting a few feet apart



Bob is positively diagnosed for COVID-19 and enters the test result in an app from his public health authority

A few days later...

Their phones exchange beacons with random Bluetooth identifiers (which change frequently)

With Bob's consent, his phone uploads the last 14 days of keys for his Bluetooth beacons to the server

Google

Alice continues her day unaware she had been near a potentially contagious person

Alice sees a notification on her phone

Sometime later...

Alice's phone periodically downloads the Bluetooth beacon keys of everyone who has tested positive for COVID-19 in her region. A match is found with Bob's random Bluetooth identifiers.



Alice's phone receives a notification with information about what to do next.



Google

	Source: (https://covid19-static.cdn-apple.com/applications/covid19/current/static/contact-tracing/pdf/ExposureNotification-FAQv1.2.pdf)

Exhibit D

to

Complaint for Patent Infringement

Claim Chart[1] for the '158 Patent

[1] Plaintiff provides this exemplary claim chart for the purposes of showing one basis of infringement of one of the Patents-in-suit by Defendant's Accused Products as defined in the Complaint. This exemplary claim chart addresses the Accused Products broadly based on the fact that the Accused Products infringe in the same general way. Plaintiff reserves its right to amend and fully provide its infringement arguments and evidence thereof until its Preliminary and Final Infringement Contentions are later produced according to the court's scheduling order in this case.

CLAIM CHART

U.S. PATENT NO. 9,402,158 B2 – CLAIM 1

Claim 1	Corresponding Structure in Accused Systems – Apple Inc.
[1a] An aggregate location dynometer in a physical wireless network server, said aggregate location dynometer comprising:	Apple Inc. ("Apple") provides a contract tracing system that utilizes Bluetooth wireless technology to determine proximity of COVID-19 positive individuals and assess the risk of infection to alert users of this risk, known as the Exposure Notifications System. *See* https://www.google.com/covid19/exposurenotifications/ and https://covid19.apple.com/contacttracing. The Exposure Notifications System together with various equipment, services, components, and/or software utilized in providing the Exposure Notifications System collectively include an aggregate location dynometer (ALD) as described by the meaning of this claim. The Exposure Notifications System is made available by a system owned and/or operated by Apple. "Because infringement liability is not dependent on ownership, e.g., use of a system can infringe (35 U.S.C. § 271), infringement is not dependent on ownership of all limitations of a claim."
[1b] a network monitor to monitor a wireless network for an indication of a potential viral event indicated by an aggregation of current locations of a plurality of physical wireless devices associated with said potential viral event; and	Apple's Exposure Notifications System has the capability to monitor a wireless network through Bluetooth beacon keys to verify and store COVID-19 positive case information, and once validated, send indication of the positive cases to users through a wireless network. This information is obtained through the system's ability to exchange Bluetooth proximity identifiers, or keys, between devices as a form of location aggregation relative to a device. A person with a positive diagnosis can upload their keys. The devices will periodically download and search the confirmed keys for matches indicating proximity to COVID-19 positive individuals. This allows the system to identify potential exposure to the virus between individuals. Applications using the Exposure Notification framework "must specify the region for which they work." *See* https://developer.apple.com/documentation/bundleresources/information_property_list/endeveloperregion. The Exposure Notification framework also contains a method to determine if the user traveled outside of their app-associated region. *See* https://developer.apple.com/documentation/exposurenotification/enmanager/3644439-getusertraveled. This demonstrates that the Exposure Notifications System has a way to access location data. The following exemplifies this limitation's existence in Accused Systems:



Source:
(https://developer.apple.com/documentation/exposurenotification/supporting_exposure_notifications_express)


Alice and Bob don't know each other, but have a lengthy conversation sitting a few feet apart
Bob is positively diagnosed for COVID-19 and enters the test result in an app from his public health authority
Their phones exchange beacons with random Bluetooth identifiers (which change frequently)
Key
Key
A few days later...
With Bob's consent, his phone uploads the last 14 days of keys for his Bluetooth beacons to the server
Apps can only get more information via user consent
Positive Test
~14 day temporary store
Google
Alice continues her day unaware she had been near a potentially contagious person
Alice sees a notification on her phone
ALERT: you have recently come in contact with someone who has tested positive for Covid-19
Tap for more information -->
Alice's phone periodically downloads the Bluetooth beacon keys of everyone who has tested positive for COVID-19 in her region. A match is found with Bob's random Bluetooth identifiers.
Anonymous identifier keys are downloaded periodically
A match is found
Sometime later...
Alice's phone receives a notification with information about what to do next.
Additional information is provided by the health authority app
Google

Source: (https://covid19-static.cdn-apple.com/applications/covid19/current/static/contact-tracing/pdf/ExposureNotification-FAQv1.2.pdf)



Source: (https://covid19-static.cdn-apple.com/applications/covid19/current/static/contact-tracing/pdf/ExposureNotification-BluetoothSpecificationv1.2.pdf?1)

[1c] a crowd risk determinant to assess said aggregation of said current locations of said plurality of physical wireless devices pertaining to said potential viral event triggered by said network monitor.	Apple's Exposure Notifications System includes an algorithm for determining risk after finding a match from the key data. The Exposure Notifications System can use the algorithm to determine exposure risk value based on risk parameters including but not limited to exposure proximity and duration. *See* https://developer.apple.com/documentation/exposurenotification/enexposureconfiguration; https://developer.apple.com/documentation/exposurenotification/enexposureconfiguration/exposure_risk_value_calculation_in_exposurenotification_version_1; and https://developer.apple.com/documentation/exposurenotification/exposure_parameter_limits. The following exemplifies this limitation's existence in Accused Systems:

13. How does the system know when I have been exposed?

The public health authority sets parameters to determine if someone has been exposed. For example, by defining the risk parameters based on estimated time the user has been in contact

Exposure Notifications - Frequently Asked Questions

with someone who has been diagnosed as positive for COVID-19 and the approximate distance between the users. Public health authorities will set a minimum threshold for time spent together.

To approximate distance, the system compares the Bluetooth signal strength between the two devices in contact. The closer the devices are, the higher the signal strength recorded. This signal strength can vary significantly based on factors like how the device is being held and as such this only provides an estimate of distance.

Source: (https://covid19-static.cdn-apple.com/applications/covid19/current/static/contact-tracing/pdf/ExposureNotification-FAQv1.2.pdf)



Source: (https://covid19-static.cdn-apple.com/applications/covid19/current/static/contact-tracing/pdf/ExposureNotification-BluetoothSpecificationv1.2.pdf?1)